



Audit Report

Global Standard for Food Safety Issue 6: July 2011

1.Audit Summary					
Company name	VION Food Group BRC Site Code 1598805				
Site name	VION Enschede BV				
Scope of audit	Deboning, cutting to specification of beef. Slicing, injecting, curing and packing of beef in bulk (chilled, dolavs and bags in crates) and in consumer packaging (chilled, vacuum).				
Exclusions from scope	None				
Audit Finish Date	2014-11-13				

2. Results								
Audit result	Certifi	cated	Audit grade		Α	Audi	t type	Announced
Audit frequency 12 month		iths	Re-audit due date		2015-11-11			
Previous audit grade B		В		Previou	ıs audit date		2013-11-08	

	Fundamental	0
Number of New Conformities	Critical	0
Number of Non-Conformities	Major	0
	Minor	8

3.Company De	3.Company Details				
Address	Het Lenfert 74 7547 SP Enschede				
Country	The Netherlands	Telephone	+31 53 486 4444		
Commercial representative Name		Email	@vionfood.com		
Technical representative Name		Email	@vionfood.nl		

LRQA Ltd Hira	mford, Middlemarc	h Business Park, Siskin Drive, Coventry, C	CV3 4FJ
English Food Version 9 December 2013	Page 1 of 56	Report No. RQA1032600 0017	Auditor:





4.Company Pro	4.Company Profile					
Plant size (metres square)	4400		No. of employees		No. of HACCP plans	3
Subcontracted pro	ocesses	No				
Other certificates I	neld	SKAL				
Regions exported	to	Europe Choose a region				
Major changes sin BRC audit	ce last	New equipment to vacuum dolavs, change in hierarchic structure (second production manager for retail)				
Company Description						

Company Description

VION Enschede B.V. is a site of VION Food Group in which beef is manufactured for retail and industry. VION Enschede is bought summer 2010 and 30 August 2010 the production is started. From employees, about ... employees are working via subcontractors mainly in production.

Main activity is the production (deboning and packing) of fresh beef for retail organisations and meat industry. There are 3 type of products (so 3 HACCP studies): slice (which can be injected), minced meat and bulk. There are 2 cutting lines and 3 packaging lines and 1 fresh meat line. Company focus is on retail customers so a major process change is being validated at this moment to alter the process more efficient and to widen the packing possibilities.

Retailers are the main customers (Western Europe with a focus on North Europe: Sweden and Danmark), but also meat industry in Western Europe mainly The Netherlands.

The production is organized from 6.00 till 15.00 in one shift. All finished products do need a heating step by the consumer or customer. Beef to be used for not heated products are released only on positive release

The production building and equipment is dated October 2009. Facility buildings are older and have no direct entrance to the production building. Authorities recognition: EG 305.

The audit was started one day after the due date, because of planning limitations at LRQA.

5.Product Characteristics						
Product categories		03 - Raw prepared products (meat and vegetarian) Category Category Category				
Finished product safety rationale Chilli		Chilling (temper	Chilling (temperature <7°C), salting, vacuum packing			
High care	No		High risk		No	
Allergens handled on site		No				

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013	Page 2 of 56	Report No. RQA1032600 0017	Auditor:	





5.Product Characteristics				
Product claims made e.g. IP, organic	Organic			
Product recalls in last 12 Months	No			
Products in production at the time of the audit	Deboning and cutting of beef quarters, labelling of beef, brine injection and slicing of beef			

6.Audit Duration Details	6.Audit Duration Details				
On-site duration	16 man hours	Duration of production facility inspection	8 man hours		
Reasons for deviation from typical or expected audit duration	no				
Next audit type selected	Announced				

Audit Duration per day						
Audit Days	Audit Dates	Audit Start Time	Audit Finish Time			
1 (start date)	2014-11-12	08.30	16.30			
2	2014-11-13	08.30	16.30			

7.Key Personnel			
Auditor Number	108137	Auditor Names and roles	A. van Bergen, Lead Assessor

Present at audit				
Note: the most senior operations manager on site should be listed first and be present at both opening & closing meetings (ref: clause 1.1.9)				
Name / Job Title	Opening Meeting	Site Inspection	Procedure Review	Closing Meeting
Director Operations	×			×
Quality Manager	Х	х	х	Х
Bedrijfsleider Uitbenen	Х	Х		Х

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ					
English Food Version 9 December 2013 Page 3 of 56 Report No. RQA1032600 0017 Auditor:					





Present at audit				
Bedrijfsleider Retail	Х	X	X	Х
HRM	Х		Х	Х
Finance	Х		Х	Х
Sales	Х		Х	Х
foreman reception carcasses		Х		
Foreman bulk packing		Х		
Foreman dispatch		Х		
Foreman Maintenance		х	х	
forewoman packing retail		х		

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ					
English Food Version 9 December 2013	Page 4 of 56	Report No. RQA1032600 0017	Auditor:		





Non-Conformity Summary Sheet

Critic	Critical or Major Non Conformities Against Fundamental Requirements						
No.	Requirement ref.	Details of non-conformity	Critical or Major?	Anticipated re-audit date			

Criti	Critical						
No.	Requirement ref.	Details of non-conformity	Anticipated re-audit date				

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ					
English Food Version 9 December 2013	Page 5 of 56	Report No. RQA1032600 0017	Auditor:		





Majo	Major							
No. Requirement ref. Details of non-conformity Corrective action taken		Root cause analysis and proposed action plan	Evidence provided document, photograph, visit/other	Date reviewed	Reviewed by			

Min	Minor								
No.	Requirement ref.	Details of non-conformity	Corrective action taken	Root cause analysis and proposed action plan	Evidence provided document, photograph, visit/other	Date reviewed	Reviewed by		
1	3.2.1	In P-ENS-NL-1017 is mentioned as reference P-Food-10014. This is wrong and should be P-VION-10015. The system to replace updated documents is not functioning.	Procedure P- ENS-NL-10017 is updated with reference P- VION-10015	Information mailed by central QA was not implemented in the local procedure. Action: mails send by QA department will be verified weekly by QA manager Vion Enschede	Document P-ENS-NL-10017	2014-12-08	Closed to be verified next audit		

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013	Page 6 of 56	Report No. RQA1032600 0017	Auditor:	





Min	or						
2	3.3.1	In production, a vacuum machine for Dolavs is introduced beginning 2014. The equipment is not listed on F-ENS-NL-10031 r1 dd 10-12-2010.	The equipment is listed on F-ENS-NL-10031 dd 27-11-2014	The document F-ENS-NL-10017 was not checked during the validation procedure. Action: verification of all related documents to complete the validation of new equipment	Document F-ENS-NL- 10017 dd 27-11- 2014	2014-12-08	Fully closed
3	3.6.1	Product specification Finished product 10292 Bio Staartstuk is not accurate and incorrect. The primary packaging material mentioned is not the same as used	Specification of article 10292 Bio Staartstuk is updated.	The specification was not the actual version. Action: All the Bio specifications will be updated in the Vion Enschede procedure.	Document (12-8-2014)	2014-12-08	Fully closed
4	4.10.3.4	Metal detection device is tested in line with test pieces which are not disinfected before usage. Contamination of the meat is possible.	The person who checked metal detection is reinstructed to disinfect test pieces before and after each check	Metal detection procedure was not complete done during testing. Action: document F- ENS-NL-10023 dd 27- 11-2014 is updated with disinfection the test pieces	Photograph Document F-ENS-NL-10023 (27-11-14)	2014-12-08	Closed to be verified next audit

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013	Page 7 of 56	Report No. RQA1032600 0017	Auditor:	





Min	Minor						
5	5.4.2	Partly used packaging materials were stored not effectively protected from contamination in the storage cell. Pimary packaging material was stored naked next to Reinstruction to the staff and it is checked daily now during ssop control F-ENS-NL-10014		Not all the packaging materials were covered in storage. Action: The staff is reinstructed and during the ssop control a check on covering the packaging materials is done daily	Document F-ENS-NL-10014 dd 27-11- 2014 Photograph	2014-12-08	Closed to be verified next audit
6	5.5.1.1	The scheduled programme of testing microbiology conform P-Food-10008 is not demonstrated. It is not clear whether this procedure and VO 2703 is met.	Implemented scheduled program of microbiology conform P- FOOD-10008	A scheduled programme was not implemented. Action: Scheduled programme implemented week 49 2014	Document: scheduled programme rest of 2014 and week 1-26 week 2015	2014-12-08	Closed to be verified next audit
7	5.5.2.1	It is not demonstrated that appropriate actions are taken after unsatisfactory results. Supplier S was tested on Listeria but it is not demonstrated that products produced out of this batch were segregated and quarantined. Also for batch Kogelbiefstuk was not demonstrated that this batch is segregated.	Vion has an Appendix specification: listeria monocytogenes on beef. Sampled batches of production are kept separate and will be shipped after result absent for listeria analyse	The batch Kogelbiefstuk was kept separate but was not marked with a label weight. Action: the sampled batches are kept separate marked with a weighing label. If there is a present listeria the label of the batch will be scanned and the complete batch will be segregated.	Vion document 'Appendix specification listeria monocytogones on beef'	2014-12-08	Closed to be verified next audit

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ					
English Food Version 9 December 2013	Page 8 of 56	Report No. RQA1032600 0017	Auditor:		





Min	Ainor Control of the								
8	7.4.2	Protective thermo jacket has pockets above the waist which are in use. Product contamination is possible.	The thermo jackets are covered by a white jacket with pockets on the inside .	One person on impedition has a thermo jacket with pockets above the waist. Action: person is reinstructed for not using protective thermo jackets with pockets above the waist anymore	Photograph	2014-12-08	Fully Closed		

LRQA Ltd Hira	amford, Middlemarc	ch Business Park, Siskin Drive, Coventry, C	CV3 4FJ
English Food Version 9 December 2013	Page 9 of 56	Report No. RQA1032600 0017	Auditor:





Detailed Audit Report

1. Senior Management Commitment

1.1 Senior management commitment and continual improvement

Policy on "Beleid & Doelstellingen is signed on 16-01-2014. The company has a management team who meets regularly. Formal communication meetings are held at several levels within the organisation; weekly MT, daily morning meetings. Minutes of department meetings are kept. Seen MT meeting minutes of 15-7, 16-9, 3-11-2014

The management review is kept at a yearly base July 2013 – June 2014 signed 16-09-2014. The reassessment together with the management review contains the verification of the HACCP system, complaints, the review of the objectives, training activities, and the preventive and corrective actions. The management review contains also evidence for continuous improvement (e.g. reduction of complaints).

Non-conformities identified at the previous BRC6 audit against the Global Standard for Food Safety are effectively corrected: The not fully closed minors are fully closed now.

The audit was started one day after the due date, because of planning limitations at LRQA.

Requirement No	REQUIREMENT	Conforms
FUNDAMENTAL Statement of Intent	The company's senior management shall demonstrate they are fully committed to the implementation of the requirements of the <i>Global Standard</i> for Food Safety and to processes which facilitate continual improvement of food safety and quality management.	Y
1.1.1	The company shall have a documented policy which states the company's intention to meet its obligation to produce safe and legal products to the specified quality and its responsibility to its customers. This shall be: signed by the person with overall responsibility for the site communicated to all staff.	Y
1.1.2	The company's senior management shall ensure that clear objectives are defined to maintain and improve the safety, legality and quality of products manufactured, in accordance with the quality policy and this Standard. These objectives shall be: documented and include targets or clear measures of success clearly communicated to relevant staff monitored and results reported at least quarterly to site senior management.	Y
1.1.3	Management review meetings attended by the site's senior management shall be undertaken at appropriate planned intervals, annually as a minimum, to review the site performance against the Standard and	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ						
English Food Version 9 December 2013	Page 10 of 56	Report No. RQA1032600 0017	Auditor:			



personnel and activities.



	objectives set in 1.1.2. The review process shall include the evaluation of:	
	 previous management review action plans and time frames results of internal, second party and/or third party audits customer complaints and results of any customer performance reviews incidents, corrective actions, out of specification results and non-conforming materials review of the management of the HACCP system resource requirements. 	
	Records of the meeting shall be documented and used to revise the objectives.	
	The decisions and actions agreed within the review process shall be effectively communicated to appropriate staff, and actions implemented within agreed time scale	
1.1.4	The company shall have a demonstrable meeting programme which enables food safety, legality and quality issues to be brought to the attention of senior management at least monthly and allows for the resolution of issues requiring immediate action.	Υ
1.1.5	The company's senior management shall provide the human and financial resources required to produce food safely in compliance with the requirements of this Standard and for the implementation of the HACCP-based food safety plan.	Υ
1.1.6	The company's senior management shall have a system in place to ensure that the company is kept informed of scientific and technical developments, industry codes of practice and all relevant legislation applicable in the country of raw material supply, production and, where known, the country where the product will be sold.	Υ
1.1.7	The company shall have a genuine, original hard copy or electronic version of the current Standard available.	Υ
1.1.8	Where the company is certificated to the Standard it shall ensure that announced recertification audits occur on or before the audit due date indicated on the certificate.	Υ
1.1.9	The most senior production or operations manager on site shall attend the opening and closing meetings of the audit for Global Standard for Food Safety certification. Relevant departmental managers or their deputies shall be available as required during the audit process.	Υ
1.1.10	The company's senior management shall ensure that the root causes of non-conformities identified at the previous audit against the Standard have been effectively addressed to prevent recurrence.	Υ
1.2	Organisational structure, responsibilities and management authority	

LRQA Ltd Hira	mford, Middlemarc	ch Business Park, Siskin Drive, Coventry, C	CV3 4FJ
English Food Version 9 December 2013	Page 11 of 56	Report No. RQA1032600 0017	Auditor:

Organisation chart is dated sept 2014. A second production leader is installed to manage the growth of





Outline of management structure: Director Operations and purchase, 2 Production Managers and 6 foremen on deboning, packing, expedition and operators, Maintenance foreman, QA manager also R&D, Sales manager, Finance manager (also IT) and HR Manager. The management team is formed by Director and managers.

Statement of Intent	The company shall have a clear organisational structure and lines of communication to enable effective management of product safety, legality and quality.	Y
1.2.1	The company shall have an organisation chart demonstrating the management structure of the company. The responsibilities for the management of activities which ensure food safety, legality and quality shall be clearly allocated and understood by the managers responsible. It shall be clearly documented who deputises in the absence of the responsible person.	Y
1.2.2	The company's senior management shall ensure that all employees are aware of their responsibilities. Where documented work instructions exist for activities undertaken, the relevant employees shall have access to these and be able to demonstrate that work is carried out in accordance with the instruction.	Y

2 The Foo	d Safety Plan – HACCP	
FUNDAMENTAL Statement of Intent	The company shall have a fully implemented and effective food safety plan based on Codex Alimentarius HACCP principles.	Υ

The HACCP system is implemented and maintained. A VION central PRP and CCP plan is the basis for the local HACCP plan.

The local HACCP plan is reassessed on 16-09-2014. It is made with input of the central HACCP plan. The HACCP system is developed by a multi-disciplinary team. Each identified hazard was reviewed and given a risk rating 1 to 9 (severity and likeliness of a hazard occurring = 3 x 3 matrix). A decision tree is used. A set of flow diagrams is part of the HACCP documentation, the steps are: Process steps in sequence: Receipt (CCP temperature), storage, cutting, metal detection, injecting (option) / slicing, packing, storage and despatch (CCP temperature). The processes were shown on a flow diagram for each process. Generic processes for example raw material receipt and storage were covered on separate flow diagrams. Checked during the audit for receiving, injecting and packing. In beginning 2013 a minced meat line is added to the production. This is the production of minced meat with 2 mincing machines, a portionizer and vacuum packers. No extra CCP's were detected.

At this moment the following CCP apply with the critical limits: Temperature incoming meat/organs: Temperature of outgoing meat/organs. Meat can come in as hanging meat, or in dolavs which is called CCP1, temperature returned products is called CCP2. CCP 3 is outgoing product. Critical temperature limits are: Organ meats: <3 °C, vacuumed organs: <2 °C; Meat: <7 °C), vacuumed meat: <6 °C. CCP monitoring has been defined and documented, records of CCP's were checked during this audit. The CCP's are checked every receiving of meat at 5 places.

Also 20 CP's apply on various prerequisite and operational processes.

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ						
English Food Version 9 December 2013	Page 12 of 56	Report No. RQA1032600 0017	Auditor:			





2.1	The HACCP food safety team – Codex Alimentarius Step 1	
2.1.1	The HACCP plan shall be developed and managed by a multi-disciplinary food safety team that includes those responsible for quality/technical, production operations, engineering and other relevant functions. The team leader shall have an in-depth knowledge of HACCP and be able to demonstrate competence and experience. The team members shall have specific knowledge of HACCP and relevant knowledge of product, process and associated hazards. In the event of the company not having appropriate in-house knowledge, external expertise may be used, but day-to-day management of the food safety system shall remain the responsibility of the company.	Υ
2.2	Prerequisite programmes	
2.2.1	The company shall establish and maintain environmental and operational programmes necessary to create an environment suitable to produce safe and legal food products (prerequisite programmes). As a guide these may include the following, although this is not an exhaustive list: cleaning and sanitising pest control maintenance programmes for equipment and buildings personal hygiene requirements staff training purchasing transportation arrangements processes to prevent cross-contamination allergen controls. The control measures and monitoring procedures for the prerequisite programmes must be clearly documented and shall be included within the development and reviews of the HACCP	Y
2.3	Describe the product – Codex Alimentarius Step 2	
2.3.1	The scope of each HACCP plan, including the products and processes covered, shall be defined. For each product or group of products a full description shall be developed, which includes all relevant information on food safety. As a guide, this may include the following, although this is not an exhaustive list: composition, e.g. raw materials, ingredients, allergens, recipe origin of ingredients physical or chemical properties that impact food safety, e.g. pH, aw treatment and processing, e.g. cooking, cooling packaging system, e.g. modified atmosphere, vacuum storage and distribution conditions, e.g. chilled, ambient target safe shelf life under prescribed storage and usage conditions instructions for use, and potential for known customer misuse, e.g.	Υ
	LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ	
English Food Vers	sion 9 December 2013 Page 13 of 56 Report No. RQA1032600 0017 Auditor:	





	storage, preparation.	
2.3.2	All relevant information needed to conduct the hazard analysis shall be collected, maintained, documented and updated. The company will ensure that the HACCP plan is based on this mayinclude the following, although this is not an exhaustive list: the latest scientific literature historical and known hazards associated with specific food products relevant codes of practice recognised guidelines food safety legislation relevant for the production and sale of products customer requirements	Y
2.4	Identify intended use – Codex Alimentarius Step 3	
2.4.1	The intended use of the product by the customer shall be described, defining the consumer target groups, including the suitability of the product for vulnerable groups of the population (e.g. infants, elderly, allergy sufferers).	Y
2.5	Construct a process flow diagram – Codex Alimentarius Step 4	
2.5.1	A flow diagram shall be prepared to cover each product, product category or process. This shall set out all aspects of the food process operation within the HACCP scope, from raw material receipt through to processing, storage and distribution. As a guide, this should include the following, although this is not an exhaustive list: • plan of premises and equipment layout • raw materials including introduction of utilities and other contact materials, e.g. water, packaging • sequence and interaction of all process steps • outsourced processes and subcontracted work • process parameters • potential for process delay • rework and recycling • low/high-care/high-risk area segregation • finished products, intermediate/semi-processed products, by-products and waste.	Y
2.6	Verify flow diagram – Codex Alimentarius Step 5	
2.6.1	The HACCP food safety team shall verify the accuracy of the flow diagrams by on-site audit and challenge at least annually. Daily and seasonal variations shall be considered and evaluated. Records of verified flow diagrams shall be maintained.	Y
2.7	List all potential hazards associated with each process step, conduct a hazard analysis any measures to control identified hazards – Codex Alimentarius Step 6, Principle 1	and consider
2.7.1	The HACCP food safety team shall identify and record all the potential hazards that are reasonably expected to occur at each step in relation to	Υ

LRQA Ltd Hira	mford, Middlemarc	h Business Park, Siskin Drive, Coventry, C	CV3 4FJ
English Food Version 9 December 2013	Page 14 of 56	Report No. RQA1032600 0017	Auditor:





	product, process and facilities. This shall include hazards present in raw materials, those introduced during the process or surviving the process steps, and allergen risks (refer to clause 5.2). It shall also take account of the preceding and following steps in the process chain.	
2.7.2	The HACCP food safety team shall conduct a hazard analysis to identify hazards which need to be prevented, eliminated or reduced to acceptable levels. Consideration shall be given to the following: likely occurrence of hazard severity of the effects on consumer safety vulnerability of those exposed survival and multiplication of micro-organisms of specific concern to the product presence or production of toxins, chemicals or foreign bodies contamination of raw materials, intermediate/semi-processed product, or finished product. Where elimination of the hazard is not practical, justification for acceptable levels of the hazard in the finished product shall be determined and	Y
	documented.	
2.7.3	The HACCP food safety team shall consider the control measures necessary to prevent or eliminate a food safety hazard or reduce it to an acceptable level. Where the control is achieved through existing prerequisite programmes, this shall be stated and the adequacy of the programme to control the hazard validated. Consideration may be given to using more than one control measure.	Y
2.8	Determine the critical control points (CCP) – Codex Alimentarius Step 7, Principle 2	
2.8.1	For each hazard that requires control, control points shall be reviewed to identify those that are critical. This requires a logical approach and may be facilitated by use of a decision tree. CCPs shall be those control points which are required in order to prevent or eliminate a food safety hazard or reduce it to an acceptable level. If a hazard is identified at a step where control is necessary for safety but the control does not exist, the product or process shall be modified at that step, or at an earlier or later step, to provide a control measure.	Υ
2.9	Establish critical limits for each CCP – Codex Alimentarius Step 8, Principle 3	
2.9.1	For each CCP, the appropriate critical limits shall be defined in order to identify clearly whether the process is in or out of control. Critical limits shall be: measurable wherever possible, e.g. time, temperature, pH supported by clear guidance or examples where measures are subjective, e.g. photographs	Y
2.9.2	The HACCP food safety team shall validate each CCP. Documented evidence shall show that the control measures selected and critical limits	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 15 of 56	Report No. RQA1032600 0017	Auditor:





	identified are capable of consistently controlling the hazard to the specified acceptable level.	
2.10	Establish a monitoring system for each CCP – Codex Alimentarius Step 9, Principle 4	
2.10.1	A monitoring procedure shall be established for each CCP to ensure compliance with critical limits. The monitoring system shall be able to detect loss of control of CCPs and wherever possible provide information in time for corrective action to be taken. As a guide, consideration may be given to the following, although this is not an exhaustive list: online measurement offlinemeasurement continuous measurement, e.g. thermographs, pH meters etc. where discontinuous measurement is used, the system shall ensure that the sample taken is representative of the batch of product.	Y
2.10.2	Records associated with the monitoring of each CCP shall include the date, time and result of measurement and shall be signed by the person responsible for the monitoring and verified, as appropriate, by an authorised person. Where records are in electronic form there shall be evidence that records have been checked and verified.	Y
	Establish a corrective action plan – Codex Alimentarius Step 10, Principle 5	
2.11.1	The HACCP food safety team shall specify and document the corrective action to be taken when monitored results indicate a failure to meet a control limit, or when monitored results indicate a trend towards loss of control. This shall include the action to be taken by nominated personnel with regard to any products that have been manufactured during the period when the process was out of control.	Y
2.12	Establish verification procedures – Codex Alimentarius Step 11, Principle 6	
2.12.1	Procedures of verification shall be established to confirm that the HACCP plan, including controls managed by prerequisite programmes, are effective. Examples of verification activities include: internal audits review of records where acceptable limits have been exceeded review of complaints by enforcement authorities or customers review of incidents of product withdrawal or recall. Results of verification shall be recorded and communicated to the HACCP food safety team.	Y
2.13	HACCP documentation and record keeping – Codex Alimentarius Step 12, Principle 7	
2.13.1	Documentation and record keeping shall be sufficient to enable the company to verify that the HACCP controls, including controls managed by prerequisite	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 16 of 56	Report No. RQA1032600 0017	Auditor:





	programmes, are in place and maintained.	
2.14	Review the HACCP plan	
2.14.1	The HACCP food safety team shall review the HACCP plan and prerequisite programmes at least annually and prior to any changes which may affect product safety. As a guide, these may include the following, although this is not an exhaustive list: change in raw materials or supplier of raw materials change in ingredients/recipe change in processing conditions or equipment change in packaging, storage or distribution conditions change in consumer use emergence of a new risk, for example adulteration of an ingredient developments in scientific information associated with ingredients, process or product. Appropriate changes resulting from the review shall be incorporated into the HACCP plan and/or prerequisite programmes, fully documented and validation recorded.	Y

3. Food safety and quality management system

3.1 Food safety and quality manual

The documented system is defined and available via . All key functions have direct access. Procedures have names by which they can be recognised. P-VION (apply to all VION plants); P-FOOD (apply to all VION Food plants); P-NLFOOD (apply to all dutch VION plants); P-ENS-NL (applies to VION Enschede).

Records of the following controls are verified as part of the vertical audit: SSOP, pre-SSOP's (to check the PRP program), CCP checks (temperature) and control metal detection (all dated 23/10/2012 as part of vertical audit).

Instructions for employees are available in 4 languages.

Minor nc 1: In P-ENS-NL-1017 is mentioned as reference P-Food-10014. This is wrong and should be P-VION-10015. The system to replace updated documents is not functioning.

Minor nc 2: In production, a vacuum machine for Dolavs is introduced beginning 2014. The equipment is not listed on F-ENS-NL-10031 v1 dd 10-12-2010.

Statement of Intent	THE COMBANY S DIOCESSES AND DIOCECULES TO MEET THE TECHNICIDENTS OF THIS	
3.1.1	The company's documented procedures, working methods and practices shall be collated in the form of a printed or electronic quality manual.	Y
3.1.2	The food safety and quality manual shall be fully implemented and the	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 17 of 56	Report No. RQA1032600 0017	Auditor:





	manual or relevant components shall be readily available to key staff.	
3.1.3	All procedures and work instructions shall be clearly legible, unambiguous, in appropriate languages and sufficiently detailed to enable their correct application by appropriate staff. This shall include the use of photographs, diagrams or other pictorial instructions where written communication alone is not sufficient (e.g. there are issues of literacy or foreign language).	Y
3.2	Documentation control	
Statement of Intent	The company shall operate an effective document control system to ensure that only the correct versions of documents, including recording forms, are available and in use.	Y
3.2.1	 The company shall have a procedure to manage documents which form part of the food safety and quality system. This shall include: a list of all controlled documents indicating the latest version number the method for the identification and authorisation of controlled documents a record of the reason for any changes or amendments to documents the system for the replacement of existing documents when these are updated. 	N
3.3	Record completion and maintenance	
Statement of Intent	The company shall maintain genuine records to demonstrate the effective control of product safety, legality and quality.	Υ
3.3.1	Records shall be legible, retained in good condition and retrievable. Any alterations to records shall be authorised and justification for alteration shall be recorded. Where records are in electronic form these shall be suitably backed up to prevent loss.	N
3.3.2	Records shall be retained for a defined period with consideration given to any legal or customer requirements and to the shelf life of the product. This shall take into account, where it is specified on the label, the possibility that shelf life may be extended by the consumer (e.g. by freezing). As a minimum, records shall be retained for the shelf life of the product plus 12 months.	Y
3.4	Internal audit	

There are schedules of internal audit against documented procedures, carried out by trained auditors of other VION companies.

Twice a year the production site in Enschede and involved departments are audited. There is a schedule for the internal audits according to procedure 'interne audits' (P-VION-10011). The audit frequencies are based on the risk of the activity to the business, the operation and the customers. A hard copy of internal audit reports is maintained. Non conformities are clearly listed with corrective actions. The last announced audits were done by on 14-2-2014 and 30-10-2014. Some minors and majors were reported. An unannounced integrity audit is done on 24-4-2014.

Audits findings mainly report on production and operation. Focus on the organizational system would also be useful.

LRQA Ltd Hira	mford, Middlemarc	h Business Park, Siskin Drive, Coventry, C	V3 4FJ
English Food Version 9 December 2013	Page 18 of 56	Report No. RQA1032600 0017	Auditor:





FUNDAMENTAL Statement of Intent	The company shall be able to demonstrate it verifies the effective application of the food safety plan and the implementation of the requirements of the Global Standard for Food Safety.	Y
3.4.1	There shall be a planned programme of internal audits with a scope which covers the implementation of the HACCP programme, prerequisite programmes and procedures implemented to achieve this Standard. The scope and frequency of the audits shall be established in relation to the risks associated with the activity and previous audit performance; all activities shall be covered at least annually.	Y
3.4.2	Internal audits shall be carried out by appropriately trained competent auditors, who are independent from the audited department.	Y
3.4.3	The internal audit programme shall be fully implemented. Internal audit reports shall identify conformity as well as non-conformity and the results shall be reported to the personnel responsible for the activity audited. Corrective actions and timescales for their implementation shall be agreed and completion of the actions verified.	Y
3.4.4	In addition to the internal audit programme there shall be a programme of documented inspections to ensure that the factory environment and processing equipment is maintained in a suitable condition for food production. These inspections shall include: • hygiene inspections to assess cleaning and housekeeping performance • fabrication inspections to identify risks to the product from the building or equipment The frequency of these inspections shall be based on risk but will be no less than once per month in open product areas.	Y
3.5	Supplier and raw material approval and performance monitoring	
3.5.1	Management of suppliers of raw materials and packaging	

Purchasing and supplier approval is at VION Food Nederland on all goods except carcasses (packaging, services, pest contractor, cleaning, transport, etc). All (other) suppliers are approved by the central VION office and entered into the IT system before they can be used. Carcass suppliers are audited regularly by VION, and corrective actions are recorded.

At the warehouse dept. incoming raw materials, packaging materials and their specifications are checked visual and temperature (CCP). Records are made. Microbiological parameters are analysed by external lab. Also supplier audits are done, generally audits are arranged VION central. Suppliers are monitored onsite by

- Every hook with beef is visual checked at delivery (and temperature is measured according F-ENS-NL-10003)
- (Morning) Inspection regarding outsourced cleaning on forms regarding pre-SSOP's

Relevant data is available, checked by vertical audit for art 10292, produced on 14-10-2014.

Statement of Intent	The company shall have an effective supplier approval and monitoring system to ensure that any potential risks from raw materials (including	Y
---------------------	--	---

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013	Page 19 of 56	Report No. RQA1032600 0017	Auditor:	





packaging) to the safety, legality and quality of the final product are understood and managed.	
The company shall undertake a documented risk assessment of each raw material or group of raw materials to identify potential risks to product safety, legality and quality. This shall take into account the potential for: allergen contamination foreign body risks microbiological contamination chemical contamination. Consideration shall also be given to the significance of a raw material to the quality of the final product. The risk assessment shall form the basis for the raw material acceptance and testing procedure and for the processes adopted for supplier approval and monitoring.	Y
The company shall have a documented supplier approval and ongoing monitoring procedure to ensure that suppliers are manufacturing products under hygienic conditions, effectively manage risks to raw material quality and safety and are operating effective traceability processes. The approval and monitoring procedure shall be based on one or a combination of: supplier audits third party audits or certification, e.g. to BRC Global Standards supplier questionnaires. Where approval is based on questionnaires, these shall be reissued at least every three years and suppliers required to notify the site of any significant changes in the interim.	Y
The procedures shall define how exceptions are handled (e.g. where raw material suppliers are prescribed by a customer or where products are purchased from agents and direct audit or monitoring has not been undertaken).	Y
Raw material and packaging acceptance and monitoring procedures	
Controls on the acceptance of raw materials shall ensure that raw materials do not compromise the safety, legality or quality of products.	Υ
The company shall have a documented procedure for the acceptance of raw materials and packaging on receipt based upon the risk assessment (3.5.1). Raw material acceptance and its release for use shall be based on one or a combination of: visual inspection on receipt certificates of conformance – specific to each consignment certificates of analysis product sampling and testing.	Y
	The company shall undertake a documented risk assessment of each raw material or group of raw materials to identify potential risks to product safety, legality and quality. This shall take into account the potential for: allergen contamination foreign body risks microbiological contamination chemical contamination. Consideration shall also be given to the significance of a raw material to the quality of the final product. The risk assessment shall form the basis for the raw material acceptance and testing procedure and for the processes adopted for supplier approval and monitoring. The company shall have a documented supplier approval and ongoing monitoring procedure to ensure that suppliers are manufacturing products under hygienic conditions, effectively manage risks to raw material quality and safety and are operating effective traceability processes. The approval and monitoring procedure shall be based on one or a combination of: supplier audits third party audits or certification, e.g. to BRC Global Standards supplier questionnaires. Where approval is based on questionnaires, these shall be reissued at least every three years and suppliers required to notify the site of any significant changes in the interim. The procedures shall define how exceptions are handled (e.g. where raw material suppliers are prescribed by a customer or where products are purchased from agents and direct audit or monitoring has not been undertaken). Raw material and packaging acceptance and monitoring procedures Controls on the acceptance of raw materials shall ensure that raw materials do not compromise the safety, legality or quality of products. The company shall have a documented procedure for the acceptance of raw materials and packaging on receipt based upon the risk assessment (3.5.1). Raw material saceptance and its release for use shall be based on one or a combination of: visual inspection on receipt certificates of conformance – specific to each consignment

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 20 of 56	Report No. RQA1032600 0017	Auditor:





	A list of raw materials and the requirements to be met for acceptance shall be available. The parameters for acceptance and frequency of testing shall be clearly defined.		
3.5.2.2	The procedures shall be fully implemented and records maintained to demonstrate the basis for acceptance of each batch of raw materials.	Υ	
3.5.3	Management of suppliers of services		
Statement of Intent	The company shall be able to demonstrate that where services are outsourced, the service is appropriate and any risks presented to food safety have been evaluated to ensure effective controls are in place.	Y	
3.5.3.1	There shall be a documented procedure for the approval and monitoring of suppliers of services. Such services shall include as appropriate: pest control laundry services contracted cleaning contracted servicing and maintenance of equipment transport and distribution off-site storage of ingredients, packaging or products laboratory testing catering services waste management.	Y	
3.5.3.2	Contracts or formal agreements shall exist with the suppliers of services which clearly define service expectations and ensure potential food safety risks associated with the service have been addressed.		
3.5.4 Management of outsourced processing			
Transport, st GFSI standa	orage and plate-freezing is outsourced to subcontracted processors which are cerds. Eg (certificate BRC Food 24/08/2015) and BRC Food 19		
Statement of Intent	T VITICIO ATTVITICATALO DIOCCOS SICOS ITI LITO ITIATIATALATO OI A DIOCAGE WITIGHT		
3.5.4.1	The company shall be able to demonstrate that where part of the production process is outsourced and undertaken off site, this has been declared to the brand owner and, where required, approval granted.		
3.5.4.2	The company shall ensure that subcontractors are approved and monitored by successful completion of either a documented site audit or third-party certification to the BRC Global Standard for Food Safety or other GFSI-recognised Standard (see Glossary).	Y	
Any outsourced processing operations shall: be undertaken in accordance with established contracts which clearly define any processing requirements and product specification		Y	

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 21 of 56	Report No. RQA1032600 0017	Auditor:





	maintain product traceability.	
3.5.4.4	The company shall establish inspection and test procedures for outsourced product on return, including visual, chemical and/or microbiological testing, dependent on risk assessment.	
3.6	Specifications	

Specifications for raw materials, packaging materials, cleaning agents and finished product are defined and managed by the involved departments. Verification in the technical department is difficult because no general overview exists.

Based upon sampling as part of the vertical audit the specifications of packaging material were available. Specifications of finished goods are available in dedicated parts of IT, software used as a planning tool.

Minor nc 3: Product specification Finished product 10292 Bio Staartstuk is not accurate and incorrect. The primary packaging material mentioned is not the same as used

Statement of Intent	Specifications shall exist for raw materials including packaging, finished products and any product or service which could affect the integrity of the finished product.	
3.6.1	Specifications for raw materials and packaging shall be adequate and accurate and ensure compliance with relevant safety and legislative requirements. The specifications shall include defined limits for relevant attributes of the material which may affect the quality or safety of the final products (e.g. chemical, microbiological or physical standards).	N
3.6.2	Manufacturing instructions and process specifications shall comply with recipes and quality criteria as detailed in agreed customer specifications.	
3.6.3	Specifications shall be available for all finished products. These shall either be in the agreed format of the customer or, in the case of branded products, include key data to meet legal requirements and assist the customer in the safe usage of the product.	
3.6.4	The company shall seek formal agreement of specifications with relevant parties. Where specifications are not formally agreed then the company shall be able to demonstrate that it has taken steps to ensure formal agreement is in place.	Y
3.6.5	Specifications shall be reviewed whenever products change (e.g. ingredients, processing method) or at least every three years. The date of review and the approval of any changes shall be recorded.	Y
	Corrective action	
FUNDAMENTAL Statement of Intent	The company shall be able to demonstrate that they use the information from identified failures in the food safety and quality management system to make necessary corrections and prevent recurrence.	Y
3.7.1	The company shall have a documented procedure for handling non-conformances identified within the scope of this Standard to include:	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
Е	nglish Food Version 9 December 2013	Page 22 of 56	Report No. RQA1032600 0017	Auditor:





- assessment of consequences by a suitably competent and authorised person
- identification of the corrective action to address the immediate issue
- identification of an appropriate timescale for correction
- identification of personnel with appropriate authority responsible for corrective action
- verification that the corrective action has been implemented and is effective
- identification of the root cause of the non-conformity and implementation of any necessary corrective action.

3.8 Control of non-conforming produ

The procedure for non-conforming product is checked during the audit and records any incidents of non-conformity. If meat falls on the floor, special educated operators can tide up this meat on a special table according P-ENS-NL-10004. Returned products are handled according P-ENS-NL-10008. All non-conforming products are categorised to CAT1. Blocked products are accompanied by form F-ENS-NL-10021.

Statement of Intent	The company shall ensure that any out-of-specification product is effectively managed to prevent release.	Y
3.8.1	 There shall be documented procedures for managing non-conforming products which include: the requirement for staff to identify and report potentially non-conforming product clear identification of non-conforming product, e.g. direct labelling or the use of IT systems secure storage to prevent accidental release, e.g. isolation areas referral to the brand owner where required defined responsibilities for decision making on the use or disposal of products appropriate to the issue, e.g. destruction, reworking, downgrading to an alternative label or acceptance by concession records of the decision on the use or disposal of the product records of destruction where product is destroyed for food safety reasons. 	Y
3.9	Traceability	

Trace test was done on 16-9-2014 on "Kogelbiefstuk" All relevant information was retrieved and procedure P-ENS-NL-10017was evaluated.

The trace test during the audit was on "BIO Staartstuk" art 10292 produced on 14-10-2014. Mass balance was correct and CCP records available. Records presented were: invoices of sales to two customers; invoices of raw material; records of incoming goods control (CCP1); stock lists; productions schedules and efficiencies; specification finished product. And also other records concerning training, prerequisite programs and IT.

FUNDAMENTAL Statement of Intent	The company shall be able to trace all raw material product lots (including packaging) from their supplier through all stages of processing and despatch to their customer and vice versa.	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ

English Food Version 9 December 2013 Page 23 of 56 Report No. RQA1032600 0017 Auditor:





3.9.1	Identification of raw materials, including primary and any other relevant packaging and processing aids, intermediate/semi-processed products, part used materials, finished products and materials pending investigation shall be adequate to ensure traceability.	
3.9.2	The company shall test the traceability system across the range of product groups to ensure traceability can be determined from raw material to finished product and vice versa, including quantity check/mass balance. This shall occur at a predetermined frequency and results shall be retained for inspection. The test shall take place at least annually. Full traceability should be achievable within four hours.	Y
3.9.3	Where rework or any reworking operation is performed, traceability shall be maintained.	Υ
3.10 Complaint handling		

Complaints are received from local sales offices and from headquarters and managed in an IT system. All complaints which are considered to be attributable to the process/ product are communicated and investigated by the quality manager. All complaints are trended and reviewed centrally ION plants). Complaints and retours together are expressed in €/1.000 ton or €/amount of orders and discussed quarterly as a KPI's in MT.

Statement of Intent	Customer complaints shall be handled effectively and information used to reduce recurring complaint levels.	Υ
3.10.1	All complaints shall be recorded, investigated and the results of the investigation and root cause of the issue recorded where sufficient information is provided. Actions appropriate to the seriousness and frequency of the problems identified shall be carried out promptly and effectively by appropriately trained staff.	Y
3.10.2	Complaint data shall be analysed for significant trends and used to implement on-going improvements to product safety, legality and quality, and to avoid recurrence. This analysis shall be made available to relevant staff.	Υ
	Management of incidents, product withdrawal and product recall	

There is a general recall procedure at VION concern (P-VION-10015 Crisis management) which covers the process and which is applicable for all operations. Also P-ENS-NL-10017 applies. A combined traceability/ recall test is reported on 16-09-2014. There were no withdrawals or recalls during the past year.

Statement of Intent	The company shall have a plan and system in place to effectively manage incidents and enable the effective withdrawal and recall of products should this be required.	Y
3.11.1	The company shall have documented procedures designed to report and effectively manage incidents and potential emergency situations that impact food safety, legality or quality. This shall include consideration of contingency plans to maintain business continuity. Incidents may include: disruption to key services such as water, energy, transport, refrigeration	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			CV3 4FJ
English Food Version 9 December 2013	Page 24 of 56	Report No. RQA1032600 0017	Auditor:





	processes, staff availability and communications events such as fire, flood or natural disaster malicious contamination or sabotage. Where products which have been released from the site may be affected by an incident, consideration shall be given to the need to withdraw or recall products.	
3.11.2	 The company shall have a documented product withdrawal and recall procedure. This shall include as a minimum: identification of key personnel constituting the recall management team, with clearly identified responsibilities guidelines for deciding whether a product needs to be recalled or withdrawn and the records to be maintained an up-to-date list of key contacts or reference to the location of such a list, e.g. recall management team, emergency services, suppliers, customers, Certification Body, regulatory authority a communication plan including the provision of information to customers, consumers and regulatory authorities in a timely manner details of external agencies providing advice and support as necessary, e.g. specialist laboratories, regulatory authority and legal expertise a plan to handle the logistics of product traceability, recovery or disposal of affected product and stock reconciliation. The procedure shall be capable of being operated at any time. 	Y
3.11.3	The product recall and withdrawal procedures shall be tested, at least annually, in a way that ensures their effective operation. Results of the test shall be retained and shall include timings of key activities. The results of the test and of any actual recall shall be used to review the procedure and implement improvements as necessary.	Y
3.11.4	In the event of a product recall, the Certification Body issuing the current certificate for the site against this Standard shall be informed within three working days of the decision to issue a recall.	Y

4. Site Standards				
4.1	4.1 External standards			
The site has been designed and constructed in 2009 for its activities at an industrial area. There are no local activities that are expected to have an adverse effect. The Maintenance department and other staff offices are in a separate building. Storage of packaging materials is the previous slaughterhouse (an older part of the building which was not in use for some years). A alteration was done past year to expand the storage volume on incoming carcasses for better canalisation.				
Statement of Intent The production site shall be of suitable size, location, construction and design to reduce the risk of contamination and facilitate the production of safe and legal finished products.		Y		

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ

English Food Version 9 December 2013 Page 25 of 56 Report No. RQA1032600 0017 Auditor:





4.1.1	Consideration shall be given to local activities and the site environment, which may have an adverse impact on finished product integrity, and measures shall be taken to prevent contamination. Where measures have been put into place to protect the site (from potential contaminants, flooding etc.), they shall be reviewed in response to any changes.			
4.1.2	The external areas shall be maintained in good order. Where buildings are surrounded by grassed or planted areas, they shall be regularly tended and well-maintained. External traffic routes under site control shall be suitably surfaced and maintained in good repair to avoid contamination of the product.			
4.1.3	The building fabric shall be maintained to minimise potential for product contamination (e.g. elimination of bird roosting sites, sealing gaps around pipes to prevent pest entry, ingress of water and other contaminants).	Y		
4.2	Security			
	es well defined and security in place with check for visitors. Separate storage take themicals, lubricants and waste. The site is recognised by NVWA (official approv			
Statement of Intent	Security systems shall ensure that products are protected from theft or malicious contamination whilst under the control of the site.	Υ		
4.2.1	The company shall undertake a documented assessment of the security arrangements and potential risks to the products from any deliberate attempt to inflict contamination or damage. Areas shall be assessed according to risk; sensitive or restricted areas shall be defined, clearly marked, monitored and controlled. Identified security arrangements shall be implemented and reviewed at least annually.			
4.2.2	Measures shall be in place to ensure only authorised personnel have access to production and storage areas and access to the site by employees, contractors and visitors shall be controlled. A visitor reporting system shall be in place. Staff shall be trained in site security procedures and encouraged to report unidentified or unknown visitors.			
4.2.3	Where required by legislation, the site shall be registered with, or be approved by, the appropriate authority.	Y		
4.3	Layout, Product Flow and Segregation			
The production and storage zones have been defined and based upon a risk assessment all zones as "Low risk areas" and "enclosed product areas". Personnel flows, material flows, services and equipm are placed such as to minimise the risk of product contamination. No high risk or high care production All produced products do need a heating step before consumption. (except beef for a client who produces filet americain; this beef is on a positive release procedure.)		equipment oduction.		
FUNDAMENTAL Statement of Intent				
4.3.1	There shall be a plan of the site which designates areas where product is at different levels of risk from contamination; that is:	Υ		

LRQA Ltd Hira	amford, Middlemard	ch Business Park, Siskin Drive, Coventry, C	CV3 4FJ
English Food Version 9 December 2013	Page 26 of 56	Report No. RQA1032600 0017	Auditor:





	 enclosed product areas low-risk areas high-care areas high-risk areas. See Appendix 2 for guidance. This shall be taken into account when determining the prerequisite programmes for the particular areas of the site.	
4.3.2	The site plan shall define: access points for personnel and travel routes location of staff facilities and routes to the facilities from places of work production process flow routes for the removal of waste routes for the movement of rework. If it is necessary to allow access through production areas, designated walkways shall be provided that ensure there is adequate segregation from materials. All facilities shall be designed and positioned, where possible, so that movement of personnel is by simple, logical routes. The movement of waste and rework shall not compromise the safety of products.	Y
4.3.3	Contractors and visitors, including drivers, shall be made aware of all procedures for access to premises and the requirements of the areas they are visiting, with special reference to hazards and potential product contamination. Contractors involved in maintenance or repair activities shall be under the supervision of a nominated person.	Y
4.3.4	In low-risk areas the process flow together with the use of demonstrably effective procedures shall be in place to minimise the risk of the contamination of raw materials, intermediate/semi-processed products, packaging and finished products.	Y
4.3.5	Where high-care areas are part of the manufacturing site there should be physical segregation between these areas and other parts of the site. Segregation shall take into account the flow of product, nature of materials, equipment, personnel, waste, airflow, air quality and utilities provision. Where physical barriers are not in place, the site shall have undertaken a full evaluation of the risks of cross-contamination and alternative effective processes shall be in place to protect products from contamination.	Na
4.3.6	Where high-risk areas are part of the manufacturing site, there shall be physical segregation between these areas and other parts of the site. Segregation shall take into account the flow of product, nature of materials, equipment, personnel, waste, airflow, air quality and utilities provision. The location of transfer points shall not compromise the segregation between high-risk areas and other areas of the factory. Practices shall be in place to minimise risk of product contamination (e.g. the disinfection of materials on entry).	Na

LRQA Ltd Hira	mford, Middlemarc	h Business Park, Siskin Drive, Coventry, C	CV3 4FJ	
English Food Version 9 December 2013	Page 27 of 56	Report No. RQA1032600 0017	Auditor:	





4.3.7	all operations to be carried out properly under safe hygienic conditions.	
4.3.8		
4.4	Building fabric Raw material handling, preparation, processing, packing and storage areas	

The fabric and internal condition of the site was suitable and satisfactory for the processes. Walls, ceilings and floors were generally suitable. Storage of packaging materials and maintenance material is separated from production.

All areas are "enclosed product" or "low risk areas".

Statement of Intent	The fabrication of the site, buildings and facilities shall be suitable for the intended purpose.			
4.4.1	Walls shall be constructed, finished and maintained to prevent the accumulation of dirt, minimise condensation and mould growth, and facilitate cleaning.	Y		
4.4.2	Floors shall be suitably hard wearing to meet the demands of the process, and withstand cleaning materials and methods. They shall be impervious and maintained in good repair.	Y		
4.4.3	Drainage , where provided, shall be sited, designed and maintained to minimise risk of product contamination and not compromise product safety. Machinery and piping shall be arranged so that, wherever feasible, process waste water goes directly to drain. Where significant amounts of water are used, or direct piping to drain is not feasible, floors shall have adequate falls to cope with the flow of any water or effluent towards suitable drainage.			
4.4.4	Where sites include high-care or high-risk facilities, there shall be a plan of the drains for these areas which shows the direction of flow and location of any equipment fitted to prevent the back up of waste water. The flow of drains shall not present a risk of contamination of the high-care/risk area.			
4.4.5	Ceilings and overheads shall be constructed, finished and maintained to prevent the risk of product contamination.			
4.4.6	Where suspended ceilings or roof voids are present, adequate access to the void shall be provided to facilitate inspection for pest activity, unless the void is fully sealed.	Y		
4.4.7	Where there is a risk to product, windows , and roof glazing which is designed to be opened for ventilation purposes, shall be adequately screened to prevent the ingress of pests.			
4.4.8	Where they pose a risk to product, glass windows shall be protected against breakage.	Y		

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013 Page 28 of 56 Report No. RQA1032600 0017 Auditor:			





4.4.9	Doors shall be maintained in good condition. External doors and dock levellers shall be close fitting or adequately proofed. External doors to open product areas shall not be opened during production periods except in emergencies. Where external doors to enclosed product areas are opened, suitable precautions shall be taken to prevent pest ingress.	Y
4.4.10	Suitable and sufficient lighting shall be provided for correct operation of processes, inspection of product and effective cleaning.	Υ
4.4.11	Where they constitute a risk to product, bulbs and strip lights – including those on electric fly-killer devices – shall be adequately protected. Where full protection cannot be provided, alternative management such as wire mesh screens or monitoring procedures shall be in place.	Y
4.4.12	Adequate ventilation and extraction shall be provided in product storage and processing environments to prevent condensation or excessive dust.	Υ
4.4.13	High-risk areas shall be supplied with sufficient changes of filtered air. The filter specification used and frequency of air changes shall be documented. This shall be based on a risk assessment, taking into account the source of the air and the requirement to maintain a positive air pressure relative to the surrounding areas.	Na
4.5	Utilities – water, ice, air and other gases	

All utilities for water, ice and heating devices (slaughter department) are within the maintenance system. Water quality of the mains is monitored by half yearly water analysis seen records of 09-10-14 and 09-04-14. A water distribution plan is available; this is in computer software which also regulates the temperature.

Machinery appears to be in a good state of maintenance. No steam or ice (except frozen CO2). The company monitors on presence of Legionella and other.

Compressed air is maintained by an external partner which is changed in the last year. Change over because of headquarter reallocation. Filters for air are changed by maintenance (an indicator is placed in the filter).

Statement of Intent	Utilities used within the production and storage areas shall be monitored to effectively control the risk of product contamination.	Υ
4.5.1	All water used as a raw material in the manufacture of processed food, the preparation of product, or for equipment or plant cleaning shall be supplied in sufficient quantity, be potable at point of use or pose no risk of contamination according to applicable legislation. The microbiological and chemical quality of water shall be analysed at least annually. The sampling points and frequency of analysis shall be based on risk, taking into account the source of the water, on-site storage and distribution facilities, previous sample history and usage.	Y
4.5.2	An up-to-date plan shall be available of the water distribution system on site, including holding tanks, water treatment and water recycling as appropriate. The plan shall be used as a basis for water sampling and the management of water quality.	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013 Page 29 of 56 Report No. RQA1032600 0017 Auditor:				





4.5.3	Where legislation specifically permits the use of water which may not be potable for initial product cleaning (e.g. for the storage/washing of fish), the water shall meet the designated legal requirement for this operation.			
4.5.4	Air, other gases and steam used directly in contact with or as an ingredient in products shall be monitored to ensure this does not represent a contamination risk. Compressed air used directly in contact with the product shall be filtered.			
4.6	Equipment			
Equipment was seen as suitably designed and used to minimise potential contamination. Relevant documents were available at the technical department, checked filter approval for filters used by . Certified by on product certification Class 2.				
Statement of Intent	All food processing equipment shall be suitable for the intended purpose and shall be used to minimise the risk of contamination of product.	Υ		
4.6.1	All equipment shall be constructed of appropriate materials. The design and placement of equipment shall ensure it can be effectively cleaned and maintained.	Y		
4.6.2	Equipment which is in direct contact with food shall be suitable for food contact and meet legal requirements where applicable.	Y		
4.7 Maintenance				
Proventive m	aintenance system is in place in eyeal with take per equipment section. Also more	nitoring on		

Preventive maintenance system is in place in excel with tabs per equipment section. Also monitoring on temperature of cooling cells by lowering set point and triggering an alarm on 08-10-2014. The new dolav vacuum equipment has no need to be maintained and is not part of the excel sheets. Daily start-up checks are recorded daily on F-ENS-NL-10033 by maintenance engineers on all departments. Also is daily checked if all TD tools are complete, clean and not damaged. Calibration of the temperature equipment of the cooling cellars could be demonstrated.

Statement of Intent	An effective maintenance programme shall be in operation for plant and equipment to prevent contamination and reduce the potential for breakdowns.	Υ
4.7.1	There shall be a documented planned maintenance schedule or condition monitoring system which includes all plant and processing equipment. The maintenance requirements shall be defined when commissioning new equipment.	Y
4.7.2	In addition to any planned maintenance programme, where there is a risk of product contamination by foreign bodies arising from equipment damage, the equipment shall be inspected at predetermined intervals, inspection results documented and appropriate action taken.	Y
4.7.3	Where temporary repairs are made, these shall be controlled to ensure the safety or legality of product is not jeopardised. These temporary measures shall be permanently repaired as soon as practicable and within a defined timescale.	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013	Page 30 of 56	Report No. RQA1032600 0017	Auditor:	





4.7.4	The company shall ensure that the safety or legality of product is not jeopardised during maintenance and subsequent cleaning operations. Maintenance work shall be followed by a documented hygiene clearance procedure, which records that product contamination hazards have been removed from machinery and equipment.	Y
4.7.5	Materials used for equipment and plant maintenance and that pose a risk by direct or indirect contact with raw materials, intermediate and finished products, such as lubricating oil, shall be food grade.	Υ
4.7.6	Engineering workshops shall be kept clean and tidy and controls shall be in place to prevent contamination risks to the product (e.g. provision of swarf mats at the entrance/exit of workshops).	Υ
4.8	Staff facilities	

There is a well arranged area for staff facility. Outdoor clothing and shoes are stored separately from work wear. For man two separate rooms and for woman one room is available. Every person has 2 lockers. Rest room and catering facilities are provided for staff. Before using the canteen relevant clothing has to be left in the changing room.

The production and storage zones have been defined and based upon a risk assessment all zones are "enclosed" or "Low risk" areas because all finished products do need a heating step before consumption. Hand-washing facilities (with hand-free soap tap operation and air dryers) were provided at entry points to production areas. Before entering production areas sole washing and hand disinfecting equipment is installed.

Smoking is only allowed in a separated area.

Statement of Intent	Staff facilities shall be sufficient to accommodate the required number of personnel, and shall be designed and operated to minimise the risk of product contamination. The facilities shall be maintained in good and clean condition.	Y
4.8.1	Designated changing facilities shall be provided for all personnel, whether staff, visitor or contractor. These shall be sited to allow direct access to the production, packing or storage areas without recourse to any external area. Where this is not possible, a risk assessment shall be carried out and procedures implemented accordingly (e.g. the provision of cleaning facilities for footwear).	Y
4.8.2	Storage facilities of sufficient size to accommodate personal items shall be provided for all personnel who work in raw material handling, preparation, processing, packing and storage areas.	Y
4.8.3	Outdoor clothing and other personal items shall be stored separately from workwear within the changing facilities. Facilities shall be available to separate clean and dirty workwear.	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013 Page 31 of 56 Report No. RQA1032600 0017 Auditor:				





4.8.4	 Where an operation includes a high-care area, personnel shall enter via a specially designated changing facility with arrangements to ensure that protective clothing will not be contaminated before entry to the high-care area. The changing facilities shall incorporate the following requirements: clear instructions for the order of changing into dedicated protective clothes to prevent the contamination of clean clothing dedicated footwear, by exception shoe coverings shall be provided for visitors only to be worn in the high-care area an effective system shall be provided to segregate areas for wearing high-care from other footwear (e.g. a barrier or bench system) or there shall be an effective boot wash on entrance to the high-care area protective clothing shall be visually distinctive from that worn in lower risk areas and shall not be worn outside of the high-care area hand-washing during the changing procedure shall be incorporated to prevent contamination of the clean protective clothing on entry to high-care areas, hand-washing and disinfection shall be provided. 	Na
4.8.5	 Where an operation includes a high-risk area, personnel shall enter via a specially designated changing facility at the entrance to the high-risk area. The changing facilities shall include the following requirements: clear instructions for the order of changing into dedicated protective clothes to prevent the contamination of clean clothing dedicated footwear shall be provided to be worn in the high-risk area an effective system shall be provided to segregate areas for wearing high-risk and other footwear, e.g. a barrier or bench system protective clothing shall be visually distinctive from that worn in other areas and shall not be worn outside of the high-risk area hand-washing during the changing procedure shall be incorporated to prevent contamination of the clean protective clothing on entry to high-risk areas, hand-washing and disinfection shall be provided. 	Na
4.8.6	Suitable and sufficient hand-washing facilities shall be provided at access to, and at other appropriate points within, production areas. Such hand-wash facilities shall provide as a minimum: sufficient quantity of water at a suitable temperature liquid soap single use towels or suitably designed and located air driers water taps with hand-free operation advisory signs to prompt hand-washing.	Y
4.8.7	Toilets shall be adequately segregated and shall not open directly into production, packing and storage areas. Toilets shall be provided with handwashing facilities comprising: basins with soap and water at a suitable temperature adequate hand-drying facilities advisory signs to prompt hand-washing.	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013 Page 32 of 56 Report No. RQA1032600 0017 Auditor:				





	Where hand-washing facilities within toilet facilities are the only facilities provided before re-entering production, the requirements of 4.8.6 shall apply and signs shall be in place to direct people to hand-wash facilities before entering production.	
4.8.8	Where smoking is allowed under national law, designated controlled smoking areas shall be provided which are both isolated from production areas to an extent that ensures smoke cannot reach the product and fitted with sufficient extraction to the exterior of the building. Adequate arrangements for dealing with smokers' waste shall be provided at smoking facilities, both inside and at exterior locations.	
4.8.9	All food brought into manufacturing premises by staff shall be appropriately stored in a clean and hygienic state. No food shall be taken into storage, processing or production areas. Where eating of food is allowed outside during breaks, this shall be in suitable designated areas with appropriate control of waste.	Υ
4.8.10	Where catering facilities are provided on the premises, they shall be suitably controlled to prevent contamination of product (e.g. as a source of food poisoning or introduction of allergenic material to the site).	Y
4.9	Chemical and physical product contamination control Raw material handling, preparation, processing, packing and storage areas	

Control of chemicals on site was organized. Separate (locked) storage facilities for e.g. cleaning chemicals, nitrate and nitrite and lubricating oil. Knifes are provided in sets. In the SSOP there is signed that no knifes are missing.

No application of glass or brittle packaging materials.

No wood is allowed at the production departments, were open product is present. Only at the end of the packing equipment wooden pallets are allowed in the packing department.

Quarterly glass audits do take place on F-ENS-NL-10031 v1 dd 10-12-2010. Seen record of 11-9-2014. Daily SSOP records seen in the vertical traceability test of and seen on de audit date on each visited department.

Statement of Intent	Appropriate facilities and procedures shall be in place to control the risk of chemical or physical contamination of product. Chemical control	
4.9.1		
4.9.1.1	Processes shall be in place to manage the use, storage and handling of non- food chemicals to prevent chemical contamination. These shall include as a minimum: an approved list of chemicals for purchase availability of material safety data sheets and specifications confirmation of suitability for use in a food processing environment avoidance of strongly scented products the labelling and/or identification of containers of chemicals at all times	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			CV3 4FJ
English Food Version 9 December 2013	Page 33 of 56	Report No. RQA1032600 0017	Auditor:





instance for building work, procedures shall be in place to prevent the risk of taint contamination of products. 4.9.2 Metal control 4.9.2.1 There shall be a documented policy for the control of the use of sharp metal implements including knives, cutting blades on equipment, needles and wires. This shall include a record of inspection for damage and the investigation of any lost items. Snap-off blade knives shall not be used. 4.9.2.2 The purchase of ingredients and packaging which use staples or other foreign-body hazards as part of the packaging materials shall be avoided. Staples and paper clips shall not be used in open product areas. Where staples or other items are present as packaging materials or closures, appropriate precautions shall be taken to minimise the risk of product contamination. 4.9.3 Glass brittle plastic, ceramics and similar materials 4.9.3.1 Glass or other brittle materials shall be excluded or protected against breakage in areas where open products are handled or there is a risk of product contamination. 4.9.3.2 Documented procedures for handling glass and other brittle materials shall be in place and implemented to ensure that necessary precautions are taken. Procedures shall include as a minimum: a list of items detailing location, number, type and condition recorded checks of condition of items, carried out at a specified frequency that is based on the level of risk to the product details on cleaning or replacing items to minimise potential for product contamination.					
instance for building work, procedures shall be in place to prevent the risk of taint contamination of products. 4.9.2 Metal control 4.9.2.1 There shall be a documented policy for the control of the use of sharp metal implements including knives, cutting blades on equipment, needles and wires. This shall include a record of inspection for damage and the investigation of any lost items. Snap-off blade knives shall not be used. 4.9.2.2 The purchase of ingredients and packaging which use staples or other foreign-body hazards as part of the packaging materials shall be avoided. Staples and paper clips shall not be used in open product areas. Where staples or other items are present as packaging materials or closures, appropriate precautions shall be taken to minimise the risk of product contamination. 4.9.3 Glass, brittle plastic, ceramics and similar materials 4.9.3.1 Glass or other brittle materials shall be excluded or protected against breakage in areas where open products are handled or there is a risk of product contamination. 4.9.3.2 Documented procedures for handling glass and other brittle materials shall be in place and implemented to ensure that necessary precautions are taken. Procedures shall include as a minimum: a list of items detailing location, number, type and condition recorded checks of condition of items, carried out at a specified frequency that is based on the level of risk to the product details on cleaning or replacing items to minimise potential for product contamination. Documented procedures detailing the action to be taken in case of breakage of glass or other brittle items shall be implemented and include the following: uquarantning the products and production area that were potentially affected cleaning the production area and authorising to continue production changing of workwear and inspection of footwear specifying those staff authorised to carry out the above points recording the breakage incident.		personnel			
There shall be a documented policy for the control of the use of sharp metal implements including knives, cutting blades on equipment, needles and wires. This shall include a record of inspection for damage and the investigation of any lost items. Snap-off blade knives shall not be used. The purchase of ingredients and packaging which use staples or other foreign-body hazards as part of the packaging materials shall be avoided. Staples and paper clips shall not be used in open product areas. Where staples or other items are present as packaging materials or closures, appropriate precautions shall be taken to minimise the risk of product contamination. 4.9.3 Glass, brittle plastic, ceramics and similar materials 4.9.3.1 Glass or other brittle materials shall be excluded or protected against breakage in areas where open products are handled or there is a risk of product contamination. 4.9.3.2 Documented procedures for handling glass and other brittle materials shall be in place and implemented to ensure that necessary precautions are taken. Procedures shall include as a minimum: a list of items detailing location, number, type and condition recorded checks of condition of items, carried out at a specified frequency that is based on the level of risk to the product details on cleaning or replacing items to minimise potential for product contamination. Documented procedures detailing the action to be taken in case of breakage of glass or other brittle items shall be implemented and include the following: quarantining the production area in spection of footwear sinspecting the production area and authorising to continue production changing of workwear and inspection of footwear specifying those staff authorised to carry out the above points recording the breakage incident.	4.9.1.2	instance for building work, procedures shall be in place to prevent the risk of			
implements including knives, cutting blades on equipment, needles and wires. This shall include a record of inspection for damage and the investigation of any lost items. Snap-off blade knives shall not be used. 4.9.2.2 The purchase of ingredients and packaging which use staples or other foreign-body hazards as part of the packaging materials shall be avoided. Staples and paper clips shall not be used in open product areas. Where staples or other items are present as packaging materials or closures, appropriate precautions shall be taken to minimise the risk of product contamination. 4.9.3 Glass, brittle plastic, ceramics and similar materials 4.9.3.1 Glass or other brittle materials shall be excluded or protected against breakage in areas where open products are handled or there is a risk of product contamination. 4.9.3.2 Documented procedures for handling glass and other brittle materials shall be in place and implemented to ensure that necessary precautions are taken. Procedures shall include as a minimum: a list of items detailing location, number, type and condition recorded checks of condition of items, carried out at a specified frequency that is based on the level of risk to the product details on cleaning or replacing items to minimise potential for product contamination. 4.9.3.3 Documented procedures detailing the action to be taken in case of breakage of glass or other brittle items shall be implemented and include the following: a quarantining the production area that were potentially affected cleaning the production area and authorising to continue production changing of workwear and inspection of footwear specifying those staff authorised to carry out the above points recording the breakage incident.	4.9.2	Metal control			
foreign-body hazards as part of the packaging materials shall be avoided. Staples and paper clips shall not be used in open product areas. Where staples or other items are present as packaging materials or closures, appropriate precautions shall be taken to minimise the risk of product contamination. 4.9.3 Glass, brittle plastic, ceramics and similar materials 4.9.3.1 Glass or other brittle materials shall be excluded or protected against breakage in areas where open products are handled or there is a risk of product contamination. 4.9.3.2 Documented procedures for handling glass and other brittle materials shall be in place and implemented to ensure that necessary precautions are taken. Procedures shall include as a minimum: a list of items detailing location, number, type and condition recorded checks of condition of items, carried out at a specified frequency that is based on the level of risk to the product details on cleaning or replacing items to minimise potential for product contamination. 4.9.3.3 Documented procedures detailing the action to be taken in case of breakage of glass or other brittle items shall be implemented and include the following: a quarantining the products and production area that were potentially affected cleaning the production area inspecting the production area and authorising to continue production changing of workwear and inspection of footwear specifying those staff authorised to carry out the above points recording the breakage incident.	4.9.2.1	implements including knives, cutting blades on equipment, needles and wires. This shall include a record of inspection for damage and the	Y		
4.9.3.1 Glass or other brittle materials shall be excluded or protected against breakage in areas where open products are handled or there is a risk of product contamination. 4.9.3.2 Documented procedures for handling glass and other brittle materials shall be in place and implemented to ensure that necessary precautions are taken. Procedures shall include as a minimum: a list of items detailing location, number, type and condition recorded checks of condition of items, carried out at a specified frequency that is based on the level of risk to the product details on cleaning or replacing items to minimise potential for product contamination. Documented procedures detailing the action to be taken in case of breakage of glass or other brittle items shall be implemented and include the following: quarantining the products and production area that were potentially affected cleaning the production area inspecting the production area and authorising to continue production changing of workwear and inspection of footwear specifying those staff authorised to carry out the above points recording the breakage incident.	4.9.2.2	foreign-body hazards as part of the packaging materials shall be avoided. Staples and paper clips shall not be used in open product areas. Where staples or other items are present as packaging materials or closures, appropriate precautions shall be taken to minimise the risk of product	Y		
breakage in areas where open products are handled or there is a risk of product contamination. 4.9.3.2 Documented procedures for handling glass and other brittle materials shall be in place and implemented to ensure that necessary precautions are taken. Procedures shall include as a minimum: a list of items detailing location, number, type and condition recorded checks of condition of items, carried out at a specified frequency that is based on the level of risk to the product details on cleaning or replacing items to minimise potential for product contamination. Documented procedures detailing the action to be taken in case of breakage of glass or other brittle items shall be implemented and include the following: quarantining the products and production area that were potentially affected cleaning the production area inspecting the production area and authorising to continue production changing of workwear and inspection of footwear specifying those staff authorised to carry out the above points recording the breakage incident.	4.9.3	Glass, brittle plastic, ceramics and similar materials			
in place and implemented to ensure that necessary precautions are taken. Procedures shall include as a minimum: a list of items detailing location, number, type and condition recorded checks of condition of items, carried out at a specified frequency that is based on the level of risk to the product details on cleaning or replacing items to minimise potential for product contamination. Documented procedures detailing the action to be taken in case of breakage of glass or other brittle items shall be implemented and include the following: quarantining the products and production area that were potentially affected cleaning the production area inspecting the production area and authorising to continue production changing of workwear and inspection of footwear specifying those staff authorised to carry out the above points recording the breakage incident.	4.9.3.1	breakage in areas where open products are handled or there is a risk of	Υ		
of glass or other brittle items shall be implemented and include the following: - quarantining the products and production area that were potentially affected - cleaning the production area - inspecting the production area and authorising to continue production - changing of workwear and inspection of footwear - specifying those staff authorised to carry out the above points - recording the breakage incident.	4.9.3.2	 in place and implemented to ensure that necessary precautions are taken. Procedures shall include as a minimum: a list of items detailing location, number, type and condition recorded checks of condition of items, carried out at a specified frequency that is based on the level of risk to the product details on cleaning or replacing items to minimise potential for product 	Y		
4.9.3.4 Products packed into glass or other brittle containers	4.9.3.3	of glass or other brittle items shall be implemented and include the following: uarantining the products and production area that were potentially affected cleaning the production area inspecting the production area and authorising to continue production changing of workwear and inspection of footwear specifying those staff authorised to carry out the above points	Y		
	4.9.3.4	Products packed into glass or other brittle containers			

	LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
E	nglish Food Version 9 December 2013	Page 34 of 56	Report No. RQA1032600 0017	Auditor:





Υ

4.9.3.4.1 The storage of the containers shall be segregated from the storage of raw materials, product or other packaging. 4.9.3.4.2 Systems shall be in place to manage container breakages between the container cleaning/inspection point and container closure. This shall include, as a minimum, documented instructions which ensure: • the removal and disposal of at-risk products in the vicinity of the breakage; this may be specific for different equipment or areas of the production line. • the effective cleaning of the line or equipment which may be contaminated by fragments of the container. Cleaning shall not result in the further dispersal of fragments, for instance by the use of high pressure water or air. • the use of dedicated, clearly identifiable cleaning equipment (e.g., colour coded) for removal of container breakages. Such equipment shall be stored separately from other cleaning equipment. • the use of dedicated, accessible lidded waste containers for the collection of damaged containers and fragments. • a documented inspection of production equipment is undertaken following the cleaning of a breakage to ensure cleaning has effectively removed any risk of further contamination. • authorisation is given for production to re-start following cleaning. • the area around the line is kept clear of broken glass. 4.9.3.4.3 Records shall be maintained of all container breakages on the line. Where no breakages have occurred during a production period, this shall also be recorded. This record shall be reviewed to identify trends and potential line or container improvements. 4.9.4 Wood 4.9.4.1 Wood 4.9.4.1 Foreign body detection and removal equipment Based upon risk analysis two metal detector devices are placed in the cutting department. After this department meat can be injected and / or sliced and packed, and there are also two metal detectors in the packing department. Fe 4,0 mm; Non FE 6,0 mm; Non FE 7,1 mm; RVS 316 8,6 mm, Testing is every 3			
container cleaning/inspection point and container closure. This shall include, as a minimum, documented instructions which ensure: * the removal and disposal of at-risk products in the vicinity of the breakage; this may be specific for different equipment or areas of the production line. * the effective cleaning of the line or equipment which may be contaminated by fragments of the container. Cleaning shall not result in the further dispersal of fragments, for instance by the use of high pressure water or air. * the use of dedicated, clearly identifiable cleaning equipment (e.g. colour coded) for removal of container breakages. Such equipment shall be stored separately from other cleaning equipment. * the use of dedicated, accessible lidded waste containers for the collection of damaged containers and fragments. * a documented inspection of production equipment is undertaken following the cleaning of a breakage to ensure cleaning has effectively removed any risk of further contamination. * authorisation is given for production to re-start following cleaning. * the area around the line is kept clear of broken glass. * Records shall be maintained of all container breakages on the line. Where no breakages have occurred during a production period, this shall also be recorded. This record shall be reviewed to identify trends and potential line or container improvements. * 4.9.4 * Wood* * A.9.4.1 * Wood* * Wood* * Sories in in good condition and free from damage or splinters which could contaminate products. * A.10 * Foreign body detection and removal equipment * Based upon risk analysis two metal detector devices are placed in the cutting department. After this department meat can be injected and / or sliced and packed, and there are also two metal detectors in the packing department. Visual checks on knives and on needle breakage are done at start up. Metal detection is arranged as a system with an alarm and a belt stop at the pro	4.9.3.4.1		Υ
breakages have occurred during a production period, this shall also be recorded. This record shall be reviewed to identify trends and potential line or container improvements. 4.9.4 Wood 4.9.4.1 Wood should not be used in open product areas except where this is a process requirement (e.g. maturation of products in wood). Where the use of wood cannot be avoided, the condition of wood shall be continually monitored to ensure it is in good condition and free from damage or splinters which could contaminate products. 4.10 Foreign body detection and removal equipment Based upon risk analysis two metal detector devices are placed in the cutting department. After this department meat can be injected and / or sliced and packed, and there are also two metal detectors in the packing department. Visual checks on knives and on needle breakage are done at start up. Metal detection is arranged as a system with an alarm and a belt stop at the production lines. Tests are done with 3 types testing rods in the cutting department: Fe 10,0 mm; Non FE 7,1 mm; RVS 316 8,7	container cleaning/inspection point and container closure. This shall include, as a minimum, documented instructions which ensure: • the removal and disposal of at-risk products in the vicinity of the breakage; this may be specific for different equipment or areas of the production line. • the effective cleaning of the line or equipment which may be contaminated by fragments of the container. Cleaning shall not result in the further dispersal of fragments, for instance by the use of high pressure water or air. • the use of dedicated, clearly identifiable cleaning equipment (e.g. colour coded) for removal of container breakages. Such equipment shall be stored separately from other cleaning equipment. • the use of dedicated, accessible lidded waste containers for the collection of damaged containers and fragments. • a documented inspection of production equipment is undertaken following the cleaning of a breakage to ensure cleaning has effectively removed any risk of further contamination. • authorisation is given for production to re-start following cleaning.		Y
Wood should not be used in open product areas except where this is a process requirement (e.g. maturation of products in wood). Where the use of wood cannot be avoided, the condition of wood shall be continually monitored to ensure it is in good condition and free from damage or splinters which could contaminate products. 4.10 Foreign body detection and removal equipment Based upon risk analysis two metal detector devices are placed in the cutting department. After this department meat can be injected and / or sliced and packed, and there are also two metal detectors in the packing department. Visual checks on knives and on needle breakage are done at start up. Metal detection is arranged as a system with an alarm and a belt stop at the production lines. Tests are done with 3 types testing rods in the cutting department: Fe 10,0 mm; Non FE 7,1 mm; RVS 316 8,7	4.9.3.4.3	breakages have occurred during a production period, this shall also be recorded. This record shall be reviewed to identify trends and potential line or	
process requirement (e.g. maturation of products in wood). Where the use of wood cannot be avoided, the condition of wood shall be continually monitored to ensure it is in good condition and free from damage or splinters which could contaminate products. 4.10 Foreign body detection and removal equipment Based upon risk analysis two metal detector devices are placed in the cutting department. After this department meat can be injected and / or sliced and packed, and there are also two metal detectors in the packing department. Visual checks on knives and on needle breakage are done at start up. Metal detection is arranged as a system with an alarm and a belt stop at the production lines. Tests are done with 3 types testing rods in the cutting department: Fe 10,0 mm; Non FE 7,1 mm; RVS 316 8,7	4.9.4	4 Wood	
Based upon risk analysis two metal detector devices are placed in the cutting department. After this department meat can be injected and / or sliced and packed, and there are also two metal detectors in the packing department. Visual checks on knives and on needle breakage are done at start up. Metal detection is arranged as a system with an alarm and a belt stop at the production lines. Tests are done with 3 types testing rods in the cutting department: Fe 10,0 mm; Non FE 7,1 mm; RVS 316 8,7	4.9.4.1	process requirement (e.g. maturation of products in wood). Where the use of wood cannot be avoided, the condition of wood shall be continually monitored to ensure it is in good condition and free from damage or splinters which	
department meat can be injected and / or sliced and packed, and there are also two metal detectors in the packing department. Visual checks on knives and on needle breakage are done at start up. Metal detection is arranged as a system with an alarm and a belt stop at the production lines. Tests are done with 3 types testing rods in the cutting department: Fe 10,0 mm; Non FE 7,1 mm; RVS 316 8,7	4.10 Foreign body detection and removal equipment		
hours and also at start and the end of the production day. Regular testing is demonstrated.	ectors in 5. Tests are 16 8,7		

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 35 of 56	Report No. RQA1032600 0017	Auditor:

Minor nc 4: Metal detection device is tested in line with test pieces, which are not disinfected before

The risk of product contamination shall be reduced or eliminated by the

effective use of equipment to remove or detect foreign bodies.

usage. Contamination of the meat is possible.

Statement

of Intent





4.40.4		
4.10.1	Foreign body detection and removal equipment	
4.10.1.1	A documented assessment in association with the HACCP study shall be carried out on each production process to identify the potential use of equipment to detect or remove foreign body contamination. Typical equipment to be considered may include: filters sieves metal detection magnets optical sorting equipment X-ray detection equipment other physical separation equipment e.g. gravity separation, fluid bed technology.	Y
4.10.1.2	The type, location and sensitivity of the detection and/or removal method shall be specified as part of the company's documented system. Industry best practice shall be applied with regard to the nature of the ingredient, material, product and/or the packed product. The location of the equipment or any other factors influencing the sensitivity of the equipment shall be validated and justified.	Y
4.10.1.3	The company shall ensure that the frequency of the testing of the foreign body detection and/or removal equipment is defined and takes into consideration: specific customer requirements the company's ability to identify, hold and prevent the release of any affected materials, should the equipment fail.	Y
4.10.1.4	Where foreign material is detected or removed by the equipment, the source of any unexpected material shall be investigated. Information on rejected materials shall be used to identify trends and where possible instigate preventive action to reduce the occurrence of contamination by the foreign material.	Y
4.10.2	Filters and sieves	
4.10.2.1	Filters and sieves used for foreign body control shall be of a specified mesh size or gauge and designed to provide the maximum practical protection for the product. Material retained or removed by the system shall be examined and recorded to identify contamination risks.	Υ
4.10.2.2	Filters and sieves shall be regularly inspected or tested for damage on a documented frequency based on risk. Records shall be maintained of the checks. Where defective filters or sieves are identified this shall be recorded and the potential for contamination of products investigated and appropriate action taken.	Y
4.10.3	Metal detectors and X-ray equipment	

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 36 of 56	Report No. RQA1032600 0017	Auditor:





4.10.3.1	Metal detection equipment shall be in place unless risk assessment demonstrates that this does not improve the protection of final products from metal contamination. Where metal detectors are not used justification shall be documented. The absence of metal detection would only normally be based on the use of an alternative, more effective, method of protection (e.g. use of X-ray, fine sieves or filtration of products).	Y
4.10.3.2	Where metal detectors or X-ray equipment is used, this shall be situated at the latest practical step in the process flow and, wherever possible, after the product has been packaged.	Y
4.10.3.3	 The metal detector or X-ray equipment shall incorporate one of the following: an automatic rejection device, for continuous in-line systems, which shall either divert contaminated product out of the product flow or to a secure unit accessible only to authorised personnel a belt stop system with an alarm where the product cannot be automatically rejected, e.g. for very large packs in-line detectors which identify the location of the contaminant shall be operated to allow effective segregation of the affected product. 	Y
4.10.3.4	The company shall establish and implement documented procedures for the operation and testing of the metal or X-ray equipment. This shall include as a minimum: responsibilities for the testing of equipment the operating effectiveness and sensitivity of the equipment and any variation to this for particular products the methods and frequency of checking the detector recording of the results of checks.	N
4.10.3.5	 Metal detector checking procedures shall be based on best practice and shall as a minimum include: use of test pieces incorporating a sphere of metal of a known diameter. The test pieces shall be marked with the size and type of test material contained. tests carried out using separate test pieces containing ferrous metal, stainless steel and typically non-ferrous metal, unless the product is within a foil container. a test that both the detection and rejection mechanisms are working effectively under normal working conditions. checks that test the memory/reset function of the metal detector by passing successive test packs through the unit. In addition, where metal detectors are incorporated on conveyors: the test piece shall be passed as close as possible to the centre of the metal detector aperture and wherever possible be carried out by inserting 	Y

	LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
Engli	sh Food Version 9 December 2013	Page 37 of 56	Report No. RQA1032600 0017	Auditor:	





	the test piece within a clearly identified sample pack of the food being produced at the time of the test. Where in-line metal detectors are used the test piece shall be placed in the product flow wherever this is possible.	
4.10.3.6	The company shall establish and implement corrective action and reporting procedures in the event of the testing procedure identifying any failure of the foreign body detector. Action shall include a combination of isolation, quarantining and re-inspection of all product produced since the last successful test.	Y
4.10.4	Magnets	
4.10.4.1	The type, location and the strength of magnets shall be fully documented. Documented procedures shall be in place for the inspection, cleaning, strength testing and integrity checks. Records of all checks shall be maintained.	Y
4.10.5	Optical sorting equipment	
4.10.5.1	Each unit shall be checked in accordance with the manufacturer's instructions or recommendations. Checks shall be documented.	Υ
4.10.6	Container cleanliness – glass jars, cans and other rigid containers	
4.10.6.1	Based on risk assessment, procedures shall be implemented to minimise foreign body contamination originating with the packaging container (e.g. jars, cans and other preformed rigid containers). This may include the use of covered conveyors, container inversion and foreign body removal through rinsing with water or air jets.	Y
4.10.6.2	The effectiveness of the container cleaning equipment shall be checked and recorded during each production. Where the system incorporates a rejection system for dirty or damaged containers, the check shall incorporate a test of both the detection and effective rejection of the test container.	Υ
4.11	Housekeeping and hygiene	

A cleaning program has been agreed with a third party and covers equipment, plant, buildings and services (with daily / weekly / monthly cleaning frequencies). Low frequent cleaning schedule (ceilings, walls above 2,5m, evaporators) assessed also. These detail the chemicals to use, precautions to take and method of cleaning. Used detergents:

. Acidity cleaning is in place once a week to avoid lime scale. 9 stages are recognised in cleaning: pre-cleaning, foam cleaning, periodical cleaning, disinfection, periodical disinfection, rinsing, manual cleaning, disassemble, assemble. Daily end of production checklists are recorded to communicate with and production (F-ENS-NL-10036)

Daily start up checks (pre SSOP's) demonstrate visual and agar measurements.

An internal facility team supports handling of waste and staff facilities (detergent, gloves, paper towels). The effectiveness of the cleaning and disinfection process is followed by hygiene audits (pre-SSOP) Swabs for CFU, pathogenic bacteria like Listeria and residue tests are taken regularly.

The dolavs and crates are washed elsewhere (arranged by transporter

). On a monthly base

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013	Page 38 of 56	Report No. RQA1032600 0017	Auditor:	





. There is a washing machine for the washing of knifes and a records of swabs are sent by circulation system to avoid cross contamination. There is no CIP. FUNDAMENTAL Υ Housekeeping and cleaning systems shall be in place which ensure Statement of Intent appropriate standards of hygiene are maintained at all times and the risk of product contamination is minimised. 4.11.1 Documented cleaning procedures shall be in place and maintained for the building, plant and all equipment. Cleaning procedures shall as a minimum include the: responsibility for cleaning item/area to be cleaned frequency of cleaning method of cleaning, including dismantling equipment for cleaning purposes where required cleaning chemicals and concentrations cleaning materials to be used cleaning records and responsibility for verification. The frequency and methods of cleaning shall be based on risk. The procedures shall be implemented to ensure appropriate standards of cleaning are achieved. 4.11.2 Limits of acceptable and unacceptable cleaning performance shall be defined, based on the potential hazards (e.g. microbiological, allergen or foreign body contamination). Acceptable levels of cleaning may be defined by visual appearance, ATP bioluminescence techniques (see Glossary), microbiological testing or chemical testing as appropriate. The cleaning and disinfection procedures and frequency shall be validated and records maintained. 4.11.3 The resources for undertaking cleaning shall be available. Where it is necessary to dismantle equipment for cleaning purposes or to enter large equipment for cleaning, this shall be appropriately scheduled and, where necessary, planned for non-production periods. Cleaning staff shall be adequately trained or engineering support provided where access within equipment is required for cleaning. 4.11.4 The cleanliness of equipment shall be checked before equipment is released back into full production. The results of checks on cleaning, including visual, analytical and microbiological checks, shall be recorded and used to identify trends in cleaning performance and instigate improvements where required. 4.11.5 Cleaning equipment shall be: fit for purpose suitably identified for intended use, e.g. colour coded or labelled cleaned and stored in a hygienic manner to prevent contamination.

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013	Page 39 of 56	Report No. RQA1032600 0017	Auditor:	





	Equipment used for cleaning in high-care and high-risk areas shall be dedicated for use in that area.	
4.11.6	Cleaning in place (CIP)	
4.11.6.1	Cleaning-in-place (CIP) facilities, where used, shall be monitored and maintained to ensure their effective operation.	Na
4.11.6.2	 A schematic plan of the layout of the CIP system shall be available. There shall be an inspection report or other verification that: systems are hygienically designed with no dead areas, limited interruptions to flow streams and good system drain ability. scavenge pumps are operated to ensure that there is no build-up of cleaning fluids in the vessels. spray balls effectively clean vessels by providing full surface coverage and are periodically inspected for blockages. Rotating spray devices should have a defined operational time. CIP equipment has adequate separation from active product lines, e.g. through the use of double seat valves, manually controlled links or blanks in pipework. The system shall be revalidated following alterations or additions to the CIP equipment. A log of changes to the CIP system shall be maintained. 	Na
4.11.6.3	 The CIP equipment shall be operated to ensure effective cleaning is carried out: The process parameters, time, detergent concentrations, flow rate and temperatures shall be defined to ensure removal of the appropriate target hazard, e.g. soil, allergens, vegetative microorganisms, spores. This shall be validated and records of the validation maintained. Detergent concentrations shall be checked routinely. Process verification shall be undertaken by analysis of rinse waters and/or first product through the line for the presence of cleaning fluids or by tests of ATP (bioluminescence techniques) allergens or microorganisms as appropriate. Detergent tanks shall be kept stocked up and a log maintained of when these are filled and emptied. Recovered pre-rinse solutions shall be monitored for a build-up of carry-over from the detergent tanks. Filters, where fitted, shall be cleaned and inspected at a defined frequency. 	Na
4.12	Waste/waste disposal	
handling of ca	es of waste are defined. Correct collection and identification was demonstrated. Lategorised meat (CAT1) is collected by a licensed company, there is no feed applies collected on call separately by	
Statement of Intent	Waste disposal shall be managed in accordance with legal requirements and to prevent accumulation, risk of contamination and the attraction of pests.	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013	Page 40 of 56	Report No. RQA1032600 0017	Auditor:	





4.12.1		1
	Where licensing is required for the disposal of categorised waste, it shall be removed by licensed contractors and records of disposal shall be maintained and available for audit.	Y
4.12.2	Food products intended to be supplied for animal feed shall be segregated from waste and managed in accordance with relevant legislative requirements.	
4.12.3	External waste collection containers and rooms housing waste facilities shall be managed to minimise risk. These shall be:	
	 clearly identified designed for ease of use and effective cleaning well-maintained to allow cleaning and, where required, disinfection emptied at appropriate frequencies covered or doors kept closed as appropriate. 	
4.12.4	If unsafe products or substandard trademarked materials are transferred to a third party for destruction or disposal, that third party shall be a specialist in secure product or waste disposal and shall provide records which includes the quantity of waste collected for destruction or disposal.	Y
4.13	Pest control	
		y the pest
to the plan a to manage a	ere was a switch to	according of iers.
to the plan a to manage a	ue to central agreements. In storage departments mice baits are placed (non tox) is seen in the technical department. The plan is part of the online facility services and control the pest operation. The service is part of the yearly evaluation of supple	according of iers.
contractor do to the plan a to manage a An in depth s	the to central agreements. In storage departments mice baits are placed (non tox) is seen in the technical department. The plan is part of the online facility services of a control the pest operation. The service is part of the yearly evaluation of supplications using the integration 2014-7 and 2 inspections were carried out. The whole site shall have an effective preventive pest control programme in place to minimise the risk of infestation and there shall be the resources available to rapidly respond to any issues which occur to prevent risk to	according of iers.





	dedicated locked facilities are used for the storage of pesticides.	
4.13.3	Pest control documentation and records shall be maintained. This shall include as a minimum: an up-to-date plan of the full site identifying numbered pest control device locations identification of the baits and/or monitoring devices on site clearly defined responsibilities for site management and for the contractor details of pest control products used, including instructions for their effective use and action to be taken in case of emergencies any observed pest activity details of pest control treatments undertaken.	Y
4.13.4	Bait stations shall be robust, of tamper resistant construction, secured in place and appropriately located to prevent contamination risk to product. Missing bait boxes shall be recorded, reviewed and investigated. Toxic rodent baits shall not be used within production areas or storage areas where open product is present except when treating an active infestation.	Y
4.13.5	Fly-killing devices and/or pheromone traps shall be correctly sited and operational. If there is a danger of insects being expelled from a fly-killing extermination device and contaminating the product, alternative systems and equipment shall be used.	Y
4.13.6	In the event of infestation, or evidence of pest activity, immediate action shall be taken to eliminate the hazard. Any potentially affected products should be subject to the non-conforming product procedure.	Y
4.13.7	Records of pest control inspections, pest proofing and hygiene recommendations and actions taken shall be maintained. It shall be the responsibility of the company to ensure all of the relevant recommendations made by their contractor or in-house expert are carried out in a timely manner.	Y
4.13.8	An in-depth, documented pest control survey shall be undertaken at a frequency based on risk, but typically quarterly, by a pest control expert to review the pest control measures in place. The timing of the survey shall be such as to allow access to equipment for inspection where a risk of stored product insect infestation exists.	Y
4.13.9	Results of pest control inspections shall be assessed and analysed for trends on a regular basis, but as a minimum: in the event of an infestation annually	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
English Food Version 9 December 2013	Page 42 of 56	Report No. RQA1032600 0017	Auditor:	





	This shall include a catch analysis from trapping devices to identify problem areas. The analysis shall be used as a basis for improving the pest control procedures.			
4.14	Storage facilities			
established (another area separate area	At the production facility several cooling areas have been defined. Control of temperatures was established (only cooled) including temperature alarm settings. Alarms are monthly tested (ever another area). Also meat can need some days for ripening, this is done at the location Ensched separate area of the building (the previous slaughter house) is applied for the storage of package supporting materials. No outside storage.			
Statement of Intent	All facilities used for the storage of ingredients, in-process product and finished products shall be suitable for its purpose.	Y		
4.14.1	Documented procedures to maintain product safety and quality during storage shall be developed on the basis of risk assessment, understood by relevant staff and implemented accordingly. These may include as appropriate:			
	 managing chilled and frozen product transfer between temperature controlled areas segregation of products where necessary to avoid cross-contamination (physical, microbiological or allergens) or taint uptake storing materials off the floor and away from walls specific handling or stacking requirements to prevent product damage. 	Y		
4.14.2	Where temperature control is required, the storage area shall be capable of maintaining product temperature within specification and operated to ensure specified temperatures are maintained. Temperature recording equipment with suitable temperature alarms shall be fitted to all storage facilities or there shall be a system of recorded manual temperature checks, typically on at least a four-hourly basis or at a frequency which allows for intervention before product temperatures exceed defined limits for the safety, legality or quality of products.	Y		
4.14.3	Where controlled atmosphere storage is required, the storage conditions shall be specified and effectively controlled. Records shall be maintained of the storage conditions.	Y		
4.14.4	Where storage outside is necessary, items shall be protected from contamination and deterioration.	Y		
4.14.5	Receipt documents and/or product identification shall facilitate correct stock rotation of raw materials, intermediate products and finished products in storage and ensure materials are used in the correct order in relation to their manufacturing date and within the prescribed shelf life.	Y		
4.15	Dispatch and transport			

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ					
English Food Version 9 December 2013	English Food Version 9 December 2013 Page 43 of 56 Report No. RQA1032600 0017 Auditor:				





Dispatch and release of products is based upon temperature measurements at CCP level (meat temperature). There's a list of approved transport companies as prescribed by headquarters. All GFSI approved.

Trucks are inspected at hygiene and temperature before loading. Results of this inspection are recorded at the CP control forms.

Statement of Intent	Procedures shall be in place to ensure that the management of dispatch and of the vehicles and containers used for transporting products from the site do not present a risk to the safety or quality of the products.	Y
4.15.1	Documented procedures to maintain product safety and quality during loading and transportation shall be developed and implemented. These may include as appropriate: controlling temperature of loading dock areas the use of covered bays for vehicle loading or unloading securing loads on pallets to prevent movement during transit inspection of loads prior to dispatch.	Y
4.15.2	Traceability shall be ensured during transportation. There shall be a clear record of dispatch and receipt of goods and materials demonstrating that sufficient checks have been completed during the transfer of goods.	Y
4.15.3	All vehicles or containers used for the dispatch of products shall be inspected prior to loading to ensure that they are fit for purpose. This shall ensure that they are: in a suitably clean condition free from strong odours which may cause taint to products suitably maintained to prevent damage to products during transit equipped to ensure any temperature requirements can be maintained. Records of inspections shall be maintained.	Y
4.15.4	Where temperature control is required, the transport shall be capable of maintaining product temperature within specification, under minimum and maximum load. Temperature data-logging devices which can be interrogated to confirm time/temperature conditions or a system to verify and record at predetermined frequencies the correct operation of refrigeration equipment shall be used and records maintained.	Y
4.15.5	Maintenance systems and documented cleaning procedures shall be maintained for all vehicles and equipment used for loading/unloading (e.g. hoses connecting to silo installations). There shall be records of the measures taken.	Υ
4.15.6	The company shall have documented procedures for the transport of products, which shall include: any restrictions on the use of mixed loads requirements for the security of products during transit, particularly when	Y

LRQA Ltd Hira	amford, Middlemard	ch Business Park, Siskin Drive, Coventry, C	CV3 4FJ
English Food Version 9 December 2013	Page 44 of 56	Report No. RQA1032600 0017	Auditor:





	vehicles are parked and unattended clear instructions in the case of vehicle breakdown, accident or failure of refrigeration systems which ensure the safety of the products is assessed and records maintained.	
4.15.7	Where the company employs third-party contractors, all the requirements specified in this section shall be clearly defined in the contract and verified or the contracted company shall be certificated to the Global Standard for Storage and Distribution or similar internationally recognised Standard.	Y

5. Product control Process improvements are done based upon investment projects. The product development process is centrally organised within the VION Food organisation. Equipment to vacumise dolavs is installed last march after validation also on shelf life. There are no product claims other than organic. Also legislation 1760/2000 on "country of birth, breed and slaughter" applies. Statement Product design and development procedures shall be in place for new Υ of Intent products or processes and any changes to product, packaging or manufacturing processes to ensure that safe and legal products are produced. 5.1.1 The company shall provide clear guidelines on any restrictions to the scope of new product developments to control the introduction of hazards which would be unacceptable to the company or customers (e.g. the introduction of allergens, glass packaging or microbiological risks). 5.1.2 All new products and changes to product formulation, packaging or methods of processing shall be formally approved by the HACCP team leader or authorised HACCP committee member. This shall ensure that hazards have been assessed and suitable controls, identified through the HACCP system, are implemented. This approval shall be granted before products are introduced into the factory environment. 5.1.3 Trials using production equipment shall be carried out where it is necessary to validate that product formulation and manufacturing processes are capable of producing a safe product of the required quality. 5.1.4 Shelf-life trials shall be undertaken using documented protocols reflecting conditions experienced during storage and handling. Results shall be recorded and retained and shall confirm compliance with relevant Υ microbiological, chemical and organoleptic criteria. Where shelf-life trials prior to production are impractical, for instance for some long-life products, a documented science-based justification for the assigned shelf life shall be

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 45 of 56	Report No. RQA1032600 0017	Auditor:





	produced.	
5.1.5	All products shall be labelled to meet legal requirements for the designated country of use and shall include information to allow the safe handling, display, storage, preparation and use of the product within the food supply chain or by the customer. There shall be a process to verify that ingredient and allergen labelling is correct based on the product recipe.	Y
5.1.6	Where a product is designed to enable a claim to be made to satisfy a consumer group (e.g. a nutritional claim, reduced sugar), the company shall ensure that the product formulation and production process is fully validated to meet the stated claim.	Y
5.2	Management of allergens	
No allergens	onsite.	
FUNDAMENTAL Statement of Intent	The company shall have a developed system for the management of allergenic materials which minimises the risk of allergen contamination of products and meets legal requirements for labelling.	Y
5.2.1	The company shall carry out an assessment of raw materials to establish the presence and likelihood of contamination by allergens (refer to glossary). This shall include review of raw material specifications and, where required, obtain additional information from suppliers, for example through questionnaires to understand the allergen status of the raw material, its ingredients and the factory in which it is produced.	Y
5.2.2	The company shall identify and list allergen-containing materials handled on site. This shall include raw materials, processing aids, intermediate and finished products and any new product development ingredients or products.	Na
5.2.3	A documented risk assessment shall be carried out to identify routes of contamination and establish documented policies and procedures for handling raw materials, intermediate and finished products to ensure cross-contamination is avoided. This shall include: consideration of the physical state of the allergenic material, i.e. powder, liquid, particulate identification of potential points of cross-contamination through the process flow assessment of the risk of allergen cross-contamination at each process step identification of suitable controls to reduce or eliminate the risk of cross-contamination.	Na
5.2.4	Documented procedures shall be established to ensure the effective management of allergenic materials to prevent cross-contamination into	Na

LRQA Ltd Hira	amford, Middlemarc	ch Business Park, Siskin Drive, Coventry, C	CV3 4FJ
English Food Version 9 December 2013	Page 46 of 56	Report No. RQA1032600 0017	Auditor:





	products not containing the allergen. This shall include as appropriate:	
	 physical or time segregation whilst allergen-containing materials are being stored, processed or packed the use of separate or additional protective over clothing when handling 	
	allergenic materials	
	 use of identified, dedicated equipment and utensils for processing scheduling of production to reduce changes between products containing 	
	 an allergen and products not containing the allergen systems to restrict the movement of airborne dust containing allergenic material 	
	 waste handling and spillage controls restrictions on food brought onto site by staff, visitors, contractors and for catering purposes. 	
5.2.5	Where rework is used, or reworking operations carried out, procedures shall be implemented to ensure rework containing allergens is not used in products that do not already contain the allergen.	Na
5.2.6	Where the nature of the production process is such that cross-contamination from an allergen cannot be prevented, a warning shall be included on the label. National guidelines or codes of practice shall be used when making such a warning statement.	Na
5.2.7	Where a claim is made regarding the suitability of a food for allergy or food sensitivity sufferers, the company shall ensure that the production process is fully validated to meet the stated claim. This shall be documented.	Na
5.2.8	Equipment or area cleaning procedures shall be designed to remove or reduce to acceptable levels any potential cross-contamination by allergens. The cleaning methods shall be validated to ensure they are effective and the effectiveness of the procedure routinely verified. Cleaning equipment used to clean allergenic materials shall either be identifiable and specific for allergen use, single use, or effectively cleaned after use.	Na
5.2.9	All relevant personnel, including engineers, temporary staff and contractors, shall have received general allergen awareness training and be trained in the company's allergen-handling procedures.	Na
5.2.10	An effective system of documented checks shall be in place at line start-up, following product changeover and changes in batches of packaging to ensure that the labels applied are correct for the products packed.	Na
5.3	Provenance, assured status and claims of identity preserved materials	
	and correct identification is established for organic beef (SKAL certificate 687910 and arrangements are made for 1760/2000 to canalise "country of birth, breed ar	
Statement of Intent	Systems of traceability, identification and segregation of raw materials, intermediate and finished products shall be in place to ensure that all claims	Y

LRQA Ltd Hira	amford, Middlemarc	ch Business Park, Siskin Drive, Coventry, C	CV3 4FJ
English Food Version 9 December 2013	Page 47 of 56	Report No. RQA1032600 0017	Auditor:





		relating to provenance or assured status can be substantiated.	
5.3.1	Where claims are to be made on finished packs about the provenance, assured or 'identity preserved' status (see Glossary) of raw materials used, the status of each batch of the raw material shall be verified and records maintained.		Y
5.3.2		Where a claim is made relating to the provenance, assured or identity preserved status of a product or ingredient, the facility shall maintain purchasing records, traceability of raw material usage and final product packing records to substantiate claims. The company shall undertake documented mass balance tests at least every six months and at a frequency to meet the particular scheme requirements.	Υ
5.3.3	The process flow for the production of products where claims are made shall be documented and potential areas for contamination or loss of identity identified. Appropriate controls shall be established to ensure the integrity of the product claims.		Y
5.4		Product Packaging	

Packaging materials are stored separately from production materials and partly used packaging should be covered prior to returning to the storage area. Checked for foils from (vertical audit). In use are plastic bags in several sizes and colour and for vacuuming and normal packing. Foils for and labels with and without glue layers.

Minor nc 5: Partly used packaging materials were stored not effectively protected from contamination in the storage cell. Primary packaging material was stored naked next to additives.

Statement of Intent	Product packaging shall be appropriate for the intended use and shall be stored under conditions to minimise contamination and deterioration.	Υ
5.4.1	When purchasing or specifying food contact packaging the supplier of packaging materials shall be made aware of any particular characteristics of the food (e.g. high fat content, pH or usage conditions such as microwaving) which may affect packaging suitability. Certificates of conformity or other evidence shall be available for product packaging to confirm it conforms to relevant food safety legislation and is suitable for its intended use.	Y
5.4.2	Where appropriate, packaging shall be stored away from raw materials and finished product. Any part-used packaging materials suitable for use shall be effectively protected from contamination and clearly identified before being returned to an appropriate storage area. Obsolete packaging shall be stored in a separate area and systems shall be in place to prevent accidental use.	N
5.4.3	Product contact liners (or raw material/work-in-progress contact liners) purchased by the company shall be appropriately coloured and resistant to tearing to prevent accidental contamination.	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 48 of 56	Report No. RQA1032600 0017	Auditor:





5.5 Product inspection and laboratory testing

Product testing is with an inspected.

(of another closed VION plant). Also pH, brine, and weight are $\,$

Sub contracted analyses (microbiological, chemical) are carried out by a laboratory operating in accordance with ISO 17025. There is no lab on site.

Minor nc 6: The scheduled program of testing microbiology conform P-Food-10008 is not demonstrated. It is not clear whether this procedure and VO 2703 is met.

Minor nc 7: It is not demonstrated that appropriate actions are taken after unsatisfactory results. Supplier was tested on Listeria but it is not demonstrated that products produced out of this batch were segregated and quarantined. Also for batch Kogelbiefstuk was not demonstrated that this batch is segregated.

Statement of Intent	The company shall undertake or subcontract inspection and analyses which are critical to confirm product safety, legality and quality, using appropriate procedures, facilities and standards.	Y
5.5.1	Product inspection and testing	
5.5.1.1	There shall be a scheduled programme of testing covering products and the processing environment which may include microbiological, chemical, physical and organoleptic testing according to risk. The methods, frequency and specified limits shall be documented.	N
5.5.1.2	Test and inspection results shall be recorded and reviewed regularly to identify trends. Appropriate actions shall be implemented promptly to address any unsatisfactory results or trends.	N
5.5.1.3	The company shall ensure that a system of on-going shelf-life assessment is in place. This shall be based on risk and shall include microbiological and sensory analysis as well as relevant chemical factors such as pH and aw. Records and results from shelf life tests shall validate the shelf life period indicated on the product.	Υ
5.5.2	Laboratory testing	
5.5.2.1	Pathogen testing shall be subcontracted to an external laboratory or, where conducted internally, the laboratory facility shall be fully segregated from the manufacturing site and have operating procedures to prevent any risk of product contamination.	Υ
5.5.2.2	Where routine testing laboratories are present on a manufacturing site, they shall be located, designed and operated to eliminate potential risks to product safety. Controls shall be documented, implemented and shall include consideration of the following: design and operation of drainage and ventilation systems access and security of the facility	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 49 of 56	Report No. RQA1032600 0017	Auditor:





	 movement of laboratory personnel protective clothing arrangements processes for obtaining product samples disposal of laboratory waste. 			
5.5.2.3	Where the company undertakes or subcontracts analyses which are critical to product safety or legality, the laboratory or subcontractors shall have gained recognised laboratory accreditation or operate in accordance with the requirements and principles of ISO 17025. Documented justification shall be available where accredited methods are not undertaken.	Y		
5.5.2.4	Procedures shall be in place to ensure reliability of laboratory results, other than those critical to safety and legality specified in 5.5.2.3. These shall include: use of recognised test methods, where available documented testing procedures ensuring staff are suitably qualified and/or trained and competent to carry out the analysis required use of a system to verify the accuracy of test results, e.g. ring or proficiency testing use of appropriately calibrated and maintained equipment.	Υ		
5.6	Product release			
loading.	Product release is based upon product temperature measurements of the beef at 5 places (CCP) before loading. For selected clients there is a positive release on microbiological values (Listeria absent).			
Statement of Intent	The company shall ensure that finished product is not released unless all agreed procedures have been followed.			
5.6.1	Where products require positive release, procedures shall be in place to ensure that release does not occur until all release criteria have been completed and release authorised.	Y		

\sim	Control
h	

6.1 Controls of operations

Processes are reflected in the Process control plan. Process control is based upon the HACCP study, legal and customer requirements. Documented start up checks are applied as Pre SSOP's and during the day SSOP are reported. Records checked on the audit day and of the vertical audit. Organic is produced at the start of the day. Excel sheets are used to communicate and account for production values and identification (batches).

FUNDAMENTAL Statement of Intent	The company shall operate to documented procedures and/or work instructions that ensure the production of consistently safe and legal product with the desired quality characteristics, in full compliance with the HACCP food safety plan.	Y

LRQA Ltd Hira	amford, Middlemard	ch Business Park, Siskin Drive, Coventry, C	CV3 4FJ
English Food Version 9 December 2013	Page 50 of 56	Report No. RQA1032600 0017	Auditor:





6.1.1	Documented process specifications and work instructions shall be available for the key processes in the production of products to ensure product safety, legality and quality. The specifications as appropriate shall include: recipes – including identification of any allergens mixing instructions, speed, time equipment process settings cooking times and temperatures cooling times and temperatures labelling instructions coding and shelf life marking any additional critical control points identified in the HACCP plan.	Y
6.1.2	Process monitoring, such as of temperature, time, pressure and chemical properties, shall be implemented, adequately controlled and recorded to ensure that product is produced within the required process specification.	Y
6.1.3	In circumstances where process parameters are controlled by in-line monitoring devices, these shall be linked to a suitable failure alert system that is routinely tested.	Y
6.1.4	Where variation in processing conditions may occur within equipment critical to the safety or quality of products, the processing characteristics shall be validated at a frequency based on risk and performance of equipment (e.g. heat distribution in retorts, ovens and processing vessels; temperature distribution in freezers and cold stores).	Y
6.1.5	In the case of equipment failure or deviation of the process from specification, procedures shall be in place to establish the safety status and quality of the product to determine the action to be taken.	Y
6.1.6	Documented checks of the production line shall be carried out before commencing production and following changes of product. These shall ensure that lines have been suitably cleaned and are ready for production. Documented checks shall be carried out at product changes to ensure all products and packaging from the previous production have been removed from the line before changing to the next production.	Y
6.1.7	Documented procedures shall be in place to ensure that products are packed into the correct packaging and correctly labelled. These shall include checks at the start of packing, during the packaging run, following packaging changes and when changing batches of packaging materials, in order to ensure that correct packaging materials are used. The procedures shall also include verification of any code information or other printing carried out at the packing stage.	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 51 of 56	Report No. RQA1032600 0017	Auditor:





6.2 Quantity-weight, volume and number contro

Quantity control is done via scales at the packing department and at expedition for bulk. Planned daily checks take place (F-ENS-NL-10009) as well as regular external measurements. All products are weighed.

E-weighing is done at the packing department. Licence is in use since 2704-2011 of NMI. Injection quantity is recorded on F-ENS-NL-10025 and 10026 to record machine adjustments and monitor weight increase.

Statement of Intent	The company shall operate a quantity control system which conforms to legal requirements in the country where the product is sold and any additional industry sector codes or specified customer requirement.	Y
6.2.1	The frequency and methodology of quantity checking shall meet the requirements of appropriate legislation governing quantity verification, and records of checks shall be maintained.	Y
6.2.2	Where the quantity of the product is not governed by legislative requirements (e.g. bulk quantity), the product must conform to customer requirements and records shall be maintained.	Y
6.3	Calibration and control of measuring and monitoring devices	

Calibration procedures ensure relevant equipment is identified and regularly calibrated. Temperature devices (hand thermometers CCP and CP related) and scales (legal issue) were sampled and in found in place. Records checked vertical audit: hand thermometers used at receiving (calibrated until 03-11-2014 and present on calibration form F-ENS-NL-10020. Cooling cellars are controlled with measure devices, which are adjusted external.

Daily all weigh equipment is checked with a weight (F-ENS-NL-10009). Yearly the balances are external calibrated. Seen calibration on 13-02-2014 on scale serial number 2070881.

Statement of Intent	The company shall be able to demonstrate that measuring and monitoring equipment is sufficiently accurate and reliable to provide confidence in measurement results.	Y
6.3.1	The company shall identify and control measuring equipment used to monitor CCPs, product safety and legality. This shall include as a minimum: a documented list of equipment and its location an identification code and calibration due date prevention from adjustment by unauthorised staff protection from damage, deterioration or misuse.	Y
6.3.2	All identified measuring devices, including new equipment, shall be checked and where necessary adjusted: at a predetermined frequency, based on risk assessment to a defined method traceable to a recognised national or international Standard where possible.	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 52 of 56	Report No. RQA1032600 0017	Auditor:





	Results shall be documented. Equipment shall be readable and be of a suitable accuracy for the measurements it is required to perform.	
6.3.3	Reference measuring equipment shall be calibrated and traceable to a recognised national or international Standard and records maintained.	Y
6.3.4	Procedures shall be in place to record actions to be taken when the prescribed measuring and monitoring devices are found not to be operating within specified limits. Where the safety or legality of products is based on equipment found to be inaccurate, action shall to be taken to ensure at-risk product is not offered for sale.	Y

7. Personnel

Training7.1 Raw material handling, preparation, processing, packing and storage areas

Due to the increase in personnel a second HR officer is installed this year. HR department has its own Quality Manual, also centrally for VION locations. Training is a relevant part of the Manual. For temporary personnel, for flex, for key personnel. Records are maintained in personnel files and in an excel-sheet.

There is evidence of introduction training for new starters and refreshment training of employees. Competency training had taken place for the staff sampled (food safety and quality).

Records were sampled and available (checked for , both for CCP receiving). A good overview of given training per person is in place. All employees do have to pass a test on the hygiene rules before starting the contract. This HACCP training (with a 15 min. test) is every two year repeated (seen 28-9-2011 and 13-3-2013).

Procedure: Hygiene regulations: available in 4 languages (Dutch, German, English and Polish).

FUNDAMENTAL Statement of Intent	The company shall ensure that all personnel performing work that affects product safety, legality and quality are demonstrably competent to carry out their activity, through training, work experience or qualification.	Y
7.1.1	All relevant personnel, including temporary staff and contractors, shall be appropriately trained prior to commencing work and adequately supervised throughout the working period.	Y
7.1.2	Where personnel are engaged in activities relating to critical control points, relevant training and competency assessment shall be in place.	Y
7.1.3	The company shall put in place documented programmes covering the training needs of relevant personnel. These shall include as a minimum: identifying the necessary competencies for specific roles providing training or other action to ensure staff have the necessary competencies	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 53 of 56	Report No. RQA1032600 0017	Auditor:





	 reviewing the effectiveness of training the delivery of training in the appropriate language of trainees. 	
7.1.4	Records of all training shall be available. This shall include as a minimum: the name of the trainee and confirmation of attendance the date and duration of the training the title or course contents, as appropriate the training provider. Where training is undertaken by agencies on behalf of the company, records of the training shall be available.	Y
7.1.5	The company shall routinely review the competencies of its staff. As appropriate, it shall provide relevant training. This may be in the form of training, refresher training, coaching, mentoring or on-the-job experience.	Y
7.2	Personal hygiene Raw material handling, preparation, processing, packing and storage areas	

All personnel is instructed on the documented hygiene standard, prior to commencing work, this includes temporary personnel, visitors and contractors. The wearing of any jewellery isn't allowed. Instructions on changing before and after lunch breaks are clear.

Effectiveness of the hygiene procedures for personnel is part of the SSOP system.

Statement of Intent		The company's personal hygiene standards shall be appropriate to the products produced, documented, and adopted by all personnel, including agency staff, contractors and visitors to the production facility.	
7.2.1		 The requirements for personal hygiene shall be documented and communicated to all personnel. This shall include as a minimum the following requirements: Watches shall not be worn. Jewellery shall not be worn, with the exception of a plain wedding ring or wedding wristband. Rings and studs in exposed parts of the body, such as ears, noses, tongues and eyebrows, shall not be worn. Fingernails shall be kept short, clean and unvarnished. False fingernails shall not be permitted. Excessive perfume or aftershave shall not be worn. Compliance with the requirements shall be checked routinely. 	Y
7.2.2		Hand cleaning shall be performed on entry to the production areas and at a frequency that is appropriate to minimise the risk of product contamination.	Y
7.2.3		All cuts and grazes on exposed skin shall be covered by an appropriately coloured plaster that is different from the product colour (preferably blue) and containing a metal detectable strip. These shall be company issued and monitored. Where appropriate, in addition to the plaster, a glove shall be	Y

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 54 of 56	Report No. RQA1032600 0017	Auditor:





	worn.	
7.2.4	Where metal detection equipment is used, a sample from each batch of plasters shall be successfully tested through the equipment and records shall be kept.	Υ
7.2.5	Processes and written instructions for staff shall be in place to control the use and storage of personal medicines, so as to minimise the risk of product contamination.	Υ
7.3	Medical screening	

Employees, visitors and contractors have to complete a health questionnaire prior to entry to any production areas. Procedures are established for personnel to notify management of infectious conditions they may be suffering from or been in contact with.

The site makes all visitors, new starters and contractors aware of the need to report infectious disease during the intake by the porter before entering the site. The health and safety service physician signs declarations for each personnel under contract of VION Enschede. Declarations seen of). Persons who are suffering from relevant infectious diseases are not allowed to enter the production facilities.

Personnel should report the use of medicine to their direct leader according the house rules in the contract. More emphasis could be given.

Statement of Intent	The company shall ensure that procedures are in place to ensure that employees, agency staff, contractors or visitors are not a source of transmission of food-borne diseases to products.	
7.3.1	The company shall have a procedure which enables notification by employees, including temporary employees, of any relevant infection, disease or condition with which they may have been in contact or be suffering from.	Y
7.3.2	Where there may be a risk to product safety, visitors and contractors shall be required to complete a health questionnaire or otherwise confirm that they are not suffering from a condition which may put product safety at risk, prior to entering the raw material, preparation, processing, packing and storage areas.	
7.3.3	There shall be documented procedures for employees, contractors and visitors, relating to action to be taken where they may be suffering from or have been in contact with an infectious disease. Expert medical advice shall be sought where required.	Y
7.4	Protective clothing Employees or visitors to production areas	

The laundering of protective clothing is outsourced to a contracted and specialised laundry. The wearing of sleeves, aprons and work coats isn't allowed during eating and smoking. Disposable hair nets are in use; bear snoods are in use. Cleaning facilities are provided. Knifes and metal gloves are washed by the company at the entrance with hydrogen peroxide 35%.

LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ			
English Food Version 9 December 2013	Page 55 of 56	Report No. RQA1032600 0017	Auditor:





No aprons or jackets have outside pockets except jackets for working in low temperature.

Minor nc 8: Protective thermo jacket has pockets above the waist which are in use. Product contamination is possible.

contamination is possible.				
	ny-issued protective clothing shall be worn by employees, sitors working in or entering production areas.	Υ		
or visitors the rule work areas (e.g. relating to the works)	nall document and communicate to all employees, contractors les regarding the wearing of protective clothing in specified high-care or low-risk areas). This shall also include policies earing of protective clothing away from the production g. removal before entering toilets, use of canteen and	Y		
 is provided i is of suitable minimum co buttons) fully contains 	ng shall be available that: n sufficient numbers for each employee e design to prevent contamination of the product (as a intaining no external pockets above the waist or sewn on s all scalp hair to prevent product contamination bods for beards and moustaches where required to prevent tamination.	N		
or in-house laun effectiveness of employee is exc is to protect the	rotective clothing shall take place by an approved contracted dry using defined and verified criteria to validate the the laundering process. Washing of workwear by the reptional but shall be acceptable where the protective clothing employee from the products handled and the clothing is worn duct or low-risk areas only.	Y		
contracted laund should have a rewhich ensure: effective cleated adequate seed cleaned clot	e clothing for high-care or high-risk areas is provided by a dry, this shall be audited either directly or by a third party, or elevant certification. The laundry must operate procedures aning of the protective clothing commercially sterile following the washing and drying process egregation between dirty and cleaned clothes hes are protected from contamination until delivered to the the use of covers or bags.	Na		
gloves shall be s	ed, they shall be replaced regularly. Where appropriate, suitable for food use, of a disposable type, of a distinctive ere possible), be intact and not shed loose fibres.	Y		
laundering are p	personal protective clothing that are not suitable for provided (such as chain mail, gloves and aprons), these shall sanitised at a frequency based on risk.	Y		

	LRQA Ltd Hiramford, Middlemarch Business Park, Siskin Drive, Coventry, CV3 4FJ				
En	glish Food Version 9 December 2013	Page 56 of 56	Report No. RQA1032600 0017	Auditor:	